

# 8502SFG2V02S

NEMA Contactor, Type S, nonreversing, Size 4, 135A, 100 HP at 575 VAC, 3 phase, up to 100 kA, 3 pole, 120V coil, NEMA 1



## Principal

Product Type	Contacteur
Product Range	8502S
Contacteur Type	Non inverseur

## Complémentaire

NEMA Size	4
Rated Current	135 A
Number of Poles	3P
Maximum Voltage Rating	600 V AC
Phase	3 phases
Horsepower Rating	40 HPà 200 V AC 50 HPà 230 V AC 100 HPà 460 V AC 100 HPà 575 V AC
SCCR	Disjoncteur 225 A maximum, SCCR: 100 kA at 480 V AC Fusible J 200 A maximum, SCCR: 100 kA at 600 V AC Fusible T 200 A maximum, SCCR: 100 kA at 600 V AC Fusible RK1 200 A maximum, SCCR: 100 kA at 600 V AC Fusible RK5 200 A maximum, SCCR: 100 kA at 600 V AC
Coil Voltage	120 V AC 60 Hz 110 V AC 50 Hz
Control Circuit Type	Separate control circuit
Control Units	No control units
Pilot Light	Sans signalisation
Auxiliary Contacts	Sans
Other Equipment	Fusible non fourni
Terminal Type	Borniers à vis-étrier

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

Height	639 mm
Width	286 mm
Depth	229 mm

## Environnemental

Enclosure Type	NEMA 1 feuille d'acier peint
Certifications	UL listed file E78351 CCN NLDX CSA

## Emballage

Poids de l'emballage (Kg)	19,105 kg
Hauteur de l'emballage 1	26,924 cm
Largeur de l'emballage 1	30,226 cm
Longueur de l'emballage 1	64,262 cm

## Offre de la durabilité

Régulation REACH	<a href="#">Déclaration REACH</a>
Sans SVHC REACH	Oui
Directive RoHS UE	Non conforme
Régulation RoHS Chine	<a href="#">Déclaration RoHS pour la Chine</a> Produit en dehors du périmètre RoHS pour la Chine. Déclaration relative aux substances pour votre information.

## Garantie contractuelle

Garantie	18 months
----------	-----------