


8536SEO1V08H30

NEMA Motor Starter, Type S, nonreversing, Size 3, 90A, 50 HP at 460 VAC, up to 100 kA SCCR, 3 phase, 3 pole, Motor Logic, 208 VAC coil, open



Principal

Product Type	Démarreur moteur
Product Range	S
Starter Type	Non réversible

Complémentaire

NEMA Size	3
Rated Current	90 A
Number of Poles	3P
Maximum Voltage Rating	600 V AC
Phase	3 phases
Type of Overload	Solid state Motor Logic class 10/20
Horsepower Rating	25 HP à 200 V AC 30 HP à 230 V AC 50 HP à 460 V AC 50 HP à 575 V AC
SCCR	Disjoncteur 150 A maximum: 100 kA at 480 V AC Fusible J 200 A maximum: 100 kA at 600 V AC Fusible T 200 A maximum: 100 kA at 600 V AC Fusible RK1 200 A maximum: 100 kA at 600 V AC Fusible RK5 200 A maximum: 100 kA at 600 V AC
Coil Voltage	208 V AC 60 Hz
Control Circuit Type	Common control circuit
Control Units	No control units
Pilot Light	Without pilot light
Auxiliary Contacts	Sans
Terminal Type	Borniers à vis-étrier
Height	281,69 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Width	138,94 mm
Depth	165,10 mm

Environnement

Enclosure Type	Not rated (open device)
Certifications	Listé UL CSA NEMA

Emballage

Poids de l'emballage (Kg)	7,711 kg
---------------------------	----------

Offre de la durabilité

Régulation REACH	Déclaration REACH
Directive RoHS UE	Non conforme
Régulation RoHS Chine	Déclaration RoHS pour la Chine Produit en dehors du périmètre RoHS pour la Chine. Déclaration relative aux substances pour votre information.

Garantie contractuelle

Garantie	18 months
----------	-----------