

## G 20/4.00A/F

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

www.weidmueller.com

### Product image



For protection against overcurrent, we offer cartridge fuse with dimensions 5x20 mm in sizes from 100 mA to 6.3 A.

### General ordering data

Version	Miniature fuse, quick-acting, 4 A, G-Si. 5 x 20
Order No.	<a href="#">0431200000</a>
Type	G 20/4.00A/F
GTIN (EAN)	4008 190022983
Qty.	10 pièce(s)

**G 20/4.00A/F****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Caractéristiques techniques****Dimensions and weights**

Height	20 mm	Height (inches)	0,787 inch
Width	5 mm	Width (inches)	0,197 inch
Net weight	1 g		

**Material data**

Colour	Light Grey
--------	------------

**System specifications**

Version	Fuse accessories
---------	------------------

**Fuse cartridges**

Cartridge fuse	G-Si. 5 x 20	Characteristics	quick-acting
Colour	Light Grey	Current	4 A
Melting integral	10 A <sup>2</sup> s	Optical function display	No
Power output (@ 1.5 In)	2,3 W	Rated breaking capacity	1,5 kA
Version	Fuse accessories	Voltage drop	180 mV

**Rating data**

Rated voltage	250 V	Rated current	4 A
---------------	-------	---------------	-----

**Classifications**

ETIM 6.0	EC000035	ETIM 7.0	EC000035
ETIM 8.0	EC002704	ETIM 9.0	EC002704
ECLASS 9.0	27-14-20-01	ECLASS 9.1	27-14-20-01
ECLASS 10.0	27-14-20-01	ECLASS 11.0	27-14-20-01
ECLASS 12.0	27-14-20-01	ECLASS 13.0	27-14-20-01
ECLASS 14.0	27-14-20-01		

**Environmental Product Compliance**

RoHS Compliance Status	Compliant without exemption
REACH SVHC	No SVHC above 0.1 wt%

**Approvals**

ROHS	Conform
------	---------

**Downloads**

User Documentation	<a href="#">StorageConditionsTerminalBlocks</a>
Catalogues	<a href="#">Catalogues in PDF-format</a>
Brochures	