

CLI C 1-3 WS/SW B CD

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com



Similar to illustration

CLI C conductor markers are mounted on unconnected conductors. Four different sizes are available for labelling conductor cross-sections from 0.5 mm² to max. 70 mm². The markers are already printed and ready for use. Individual labelling is possible by combining the individual markers.

- Closed markers, reliable and for mounting on unconnected cables
- A special flexible bellow profile ensures a wide application range
- Fast and easy to fit – with minimal effort
- Corresponding accessories make labelling easy
- Permanent, high-quality labelling
- High contrast for optimum legibility

General ordering data

| | |
|------------|---|
| Version | CableLine, Conductor and cable markers, 2.5 - 5 mm, 3 x 4.2 mm, white |
| Order No. | 1568251022 |
| Type | CLI C 1-3 WS/SW B CD |
| GTIN (EAN) | 4032248441204 |
| Qty. | 500 pièce(s) |

CLI C 1-3 WS/SW B CD

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Caractéristiques techniques

Dimensions and weights

| | | | |
|------------|--------|-----------------|------------|
| Depth | 5 mm | Depth (inches) | 0,197 inch |
| Height | 3 mm | Height (inches) | 0,118 inch |
| Width | 4,2 mm | Width (inches) | 0,165 inch |
| Net weight | 0,08 g | | |

Temperatures

| | |
|-----------------------------|-------------|
| Operating temperature range | -30...80 °C |
|-----------------------------|-------------|

General data

| | |
|--|--------------------------------------|
| Colour | white |
| Colour of printing | black |
| Halogen | Yes |
| Material | PVC, soft, without Cadmium |
| Material colour according to resistance code | 9 |
| Number of markers per combination | 1 Reel = Conductor and cable markers |
| Number of markers per packaging unit | Form of supply Reel |
| Operating temperature range | -30...80 °C |
| Operating temperature range, max. | 80 °C |
| Operating temperature range, min. | -30 °C |
| Orientation of print | horizontal |
| Printed characters | Upper-case letters |
| Printing | B |
| Printing method | hot-embossing |
| Recommended industries | Process, Machinery |
| Type of printing | Standard |
| UL 94 flammability rating | V-0 |
| Version | CD |
| Width | 4,2 mm |

Conductor and cable markers

| | | | |
|-------------------------------|---------------------|----------------------------------|-------------------------|
| Conductor O.D. | 2.5 - 5 mm | Conductor O.D., max. | 5 mm |
| Conductor O.D., min. | 2,5 mm | Conductor cross-section, max. | 4 mm ² |
| Conductor cross-section, min. | 1,5 mm ² | Cross-section for connected wire | 1.5 - 4 mm ² |
| Halogen | Yes | | |

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 6.0 | EC001530 | ETIM 7.0 | EC001530 |
| ETIM 8.0 | EC001530 | ETIM 9.0 | EC001530 |
| ECLASS 9.0 | 27-40-04-01 | ECLASS 9.1 | 27-40-04-01 |
| ECLASS 10.0 | 27-40-04-01 | ECLASS 11.0 | 27-28-11-02 |
| ECLASS 12.0 | 27-28-11-02 | ECLASS 13.0 | 27-28-11-02 |
| ECLASS 14.0 | 27-28-11-02 | | |

Environmental Product Compliance

| | |
|------------------------|-----------------------------|
| RoHS Compliance Status | Compliant without exemption |
| REACH SVHC | No SVHC above 0.1 wt% |

Date de création 26 novembre 2024 15:18:28 CET

Niveau du catalogue 26.11.2024 / Toutes modifications techniques réservées

Fiche de données**CLI C 1-3 WS/SW B CD**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Caractéristiques techniques**Approvals**

| | |
|------|---------|
| ROHS | Conform |
|------|---------|

Downloads

| | |
|-----------------------------|--|
| Product Change Notification | PCN CableLine_DE PCN CableLine_EN |
| Catalogues | Catalogues in PDF-format |

Fiche de données

CLI C 1-3 WS/SW B CD

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Dessins



Similar to illustration