

IE-SW-EL08-8GT-MINI**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Features of EcoLine unmanaged Switch series**

- Huge variety of port count and media type enable a wide range of applications (5 to 24 ports)
- Models supporting Gigabit Ethernet including Jumbo Frame support for applications with high demand on bandwidth and latency
- Suitable for use in harsh industrial environment thanks to rugged design and wide operating temperature range of -40°C up to 75°C
- Reliable operation due to redundant voltage inputs, fault relay and LED diagnostics

General ordering data

| | |
|------------|---|
| Version | Network switch, unmanaged, Gigabit Ethernet, Number of ports: 8x RJ45, IP30, -40 °C...75 °C |
| Order No. | 2705000000 |
| Type | IE-SW-EL08-8GT-MINI |
| GTIN (EAN) | 4050118740936 |
| Qty. | 1 pièce(s) |

IE-SW-EL08-8GT-MINI

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Caractéristiques techniques

Dimensions and weights

| | | | |
|------------|-------|-----------------|------------|
| Depth | 90 mm | Depth (inches) | 3,543 inch |
| Height | 95 mm | Height (inches) | 3,74 inch |
| Width | 41 mm | Width (inches) | 1,614 inch |
| Net weight | 365 g | | |

Temperatures

| | | | |
|---------------------|----------------------------|-----------------------|----------------|
| Storage temperature | -40 °C...85 °C | Operating temperature | -40 °C...75 °C |
| Humidity | 5 to 95 % (non-condensing) | | |

EMC conformity and approvals

| | | | |
|-----------------|--|-----------|--|
| EMC standards | EN 55032, EN 55024, CISPR 32, FCC Part 15 Subpart B Class A, IEC 61000-4-2 ESD: Contact: 6 kV; Air: 10 kV, IEC 61000-4-3 RS: 80 MHz bis 1 Ghz: 3 V/m, IEC 61000-4-4 EFT: Power: 2 kV; Signal: 2 kV, IEC 61000-4-5 Surge: Power: 1 kV; Signal: 4 kV, IEC 61000-4-6 CS: 3 Vrms | Free fall | |
| Safety standard | UL 61010-1, UL 61010-2-201 | Shock | According to IEC 60068-2-31 according to IEC 60068-2-27 |
| Vibration | according to IEC 60068-2-6 | | |

Environmental conditions

| | | | |
|-----------------------------|----------------------------|--|--|
| Humidity | 5 to 95 % (non-condensing) | | |
| Operating altitude | Altitude, max. | 2 000 m | |
| | Note | in acc. with UL | |
| | Altitude, max. | 6 000 m | |
| | Note | for restrictions, see the manufacturer's declaration for operating altitude in section downloads | |
| Operating temperature, max. | 75 °C | | |
| Operating temperature, min. | -40 °C | | |
| Storage temperature, max. | 85 °C | | |
| Storage temperature, min. | -40 °C | | |

Guarantee

| | |
|---------------|---------|
| Time interval | 5 years |
|---------------|---------|

Interfaces

| | | | |
|---------------|--|-----------------|---------|
| LED indicator | Power LED: PWR1, PWR2, Port LED: LNK/ACT, 10/100/1000M (RJ45 port) | Number of ports | 8x RJ45 |
| RJ45 ports | 10/100/1000BaseT(X), auto negotiation, Full-/half-duplex mode, Auto MDI/MDI-X port | | |

Date de création 26 novembre 2024 14:04:06 CET

Niveau du catalogue 26.11.2024 / Toutes modifications techniques réservées

2

IE-SW-EL08-8GT-MINI

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Caractéristiques techniques

MTBF

| | | |
|------|------------------------------|------------------|
| MTBF | According to Standard | Telcordia SR-332 |
| | Operating time (hours), min. | 1 742 238 h |

Power supply

| | | | |
|-----------------------------|-----------------------------------|--------|--|
| Connection type | 1 removable 4-pin terminal block | | |
| Current consumption | Voltage | 12 V | |
| | Current | 0,42 A | |
| | Voltage | 24 V | |
| | Current | 0,17 A | |
| | Voltage | 48 V | |
| | Current | 0,09 A | |
| Overload current protection | Yes | | |
| Reverse polarity protection | Yes | | |
| Voltage supply | 12/24/48 V DC, 2 redundant inputs | | |
| Voltage supply range | Voltage type | DC | |
| | Voltage, min. | 10,8 V | |
| | Voltage, max. | 52,8 V | |

Switch characteristics

| | | | |
|---------------------|-----------|---------------------|------------|
| Bandwidth backplane | 16 Gbit/s | Jumbo frame support | up to 9 KB |
| MAC table size | 4 K | Packet buffer size | 1,5 Mbit |

Technical data

| | | | |
|-----------------------|------------------|-------------------|-----------|
| Housing main material | Metal | Protection degree | IP30 |
| Speed | Gigabit Ethernet | Switch | unmanaged |
| Type of mounting | DIN rail | | |

Technology

| | | | |
|----------------|--|--------------|--------------------------|
| Data switching | Store and Forward | Flow control | IEEE 802.3x flow control |
| Standard | IEEE 802.3 for 10BASE-T, IEEE 802.3u for 100BASE-TX, IEEE 802.3ab for 1000BASE-T, IEEE 802.3x for flow control | | |

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 6.0 | EC000734 | ETIM 7.0 | EC000734 |
| ETIM 8.0 | EC000734 | ETIM 9.0 | EC000734 |
| ECLASS 9.0 | 19-17-01-06 | ECLASS 9.1 | 19-17-01-06 |
| ECLASS 10.0 | 19-17-04-02 | ECLASS 11.0 | 19-17-04-02 |
| ECLASS 12.0 | 19-17-04-02 | ECLASS 13.0 | 19-17-04-02 |
| ECLASS 14.0 | 19-17-04-02 | | |

Environmental Product Compliance

| | | | |
|--------------------------------------|--|--|--|
| RoHS Compliance Status | Compliant with exemption | | |
| RoHS Exemption (if applicable/known) | 6c, 7a, 7cI | | |
| REACH SVHC | Lead 7439-92-1 Lead monoxide 1317-36-8 | | |
| SCIP | 9229992a-00b9-4096-8962-200a7f33e289 | | |

Date de création 26 novembre 2024 14:04:06 CET

Niveau du catalogue 26.11.2024 / Toutes modifications techniques réservées

3

IE-SW-EL08-8GT-MINI

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Caractéristiques techniques

Approvals

Approvals



| | |
|-------------------------|------------|
| ROHS | Conform |
| UL File Number Search | UL Website |
| Certificate no. (cULus) | E141197 |

Downloads

| | |
|---|--|
| Approval/Certificate/Document of Conformity | KC certificate EU Declaration of Conformity RCM Declaration of Conformity UK Declaration of Conformity Manufacturer's declaration for operating altitude |
| Engineering Data | CAD data – STEP |
| User Documentation | Hardware Installation Guide Application notes – Industrial Product Security Guideline |
| Catalogues | Catalogues in PDF-format |