



### Principal

Product or Component Type	Disjoncteur
Range	PowerPact P
Current Sensor Rating Range	800 A
Rated Current	800 A
Breaking Capacity	65 kAà 240 V AC 35 kA at 480 V AC 18 kAà 600 V AC
Trip Unit Technology	Électronique, ammeter, Micrologic 6.0 A, LSIG
AWG Gauge	AWG 3/0...500 kcmil (aluminium / cuivre) pour 3 câble(s)

### Complémentaire

Device Short Name	A
Certifications	CSA CEI Listé UL
Rated operational Voltage	600 V AC
Module Type	P-Frame
Mounting Location	Bolt-on
Mounting Mode	Montage de l'unité
Poles Description	3P
Circuit Breaker Rating Code	G
Continuous Current Rating	100 %
Electrical Connection	Cosses charge Cosses ligne
Tightening Torque	50 N.m pour 95...240 mm <sup>2</sup> (AWG 3/0...500 kcmil) 1,0...1,3 N.m
Height	326,64 mm
Width	210,06 mm
Depth	204,47 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Emballage

Poids de l'emballage (Kg)	14,515 kg
---------------------------	-----------

## Offre de la durabilité

Statut environnemental de l'offre	Produit Green Premium
Régulation REACH	<a href="#">Déclaration REACH</a>
Directive RoHS UE	Conforme <a href="#">Déclaration RoHS UE</a>
Sans mercure	Oui
Information sur les exemptions RoHS	Oui
Régulation RoHS Chine	<a href="#">Déclaration RoHS pour la Chine</a> Produit en dehors du périmètre RoHS pour la Chine. Déclaration relative aux substances pour votre information.
Profil environnemental	<a href="#">Profil environnemental du Produit</a>
Profil de circularité	<a href="#">Informations de fin de vie</a>
Sans PVC	Oui

## Garantie contractuelle

Garantie	18 months
----------	-----------