



Principal

Product	Single Throw Safety Switch
Disconnect Type	Fusible disconnect
Number of Poles	3
Electrical Connection	Cosses
Duty Rating	Renforcé

Complémentaire

Line Rated Current	60 A
Factory Installed Neutral	None
Mounting Type	Saillie
Voltage Rating	600 V AC/DC
Wire Size	AWG 14...AWG 3 cuivre ou aluminium
Puissance moteur hp	15 hp at 480 V AC 50...60 Hz for 3 phases motors conforming to NEC 240.6 30 hp at 480 V AC 50...60 Hz for 3 phases motors conforming to NEC 430.52 15 hp at 600 V AC 50...60 Hz for 3 phases motors conforming to NEC 240.6 50 hp at 600 V AC 50...60 Hz for 3 phases motors conforming to NEC 430.52 10 hp à 250 V DC 30 hp at 600 V DC
Hauteur	444,50 mm
Largeur	266,70 mm
Profondeur	162,05 mm
Couple de serrage	5,65 N.m (AWG 3) 5,08 N.m (AWG 6...AWG 4) 4,52 N.m (AWG 8) 5,65 N.m pour 2,06...5,261 mm ² (AWG 14...AWG 10) 5,65 N.m (AWG 14...AWG 10)

Environnement

Certifications	CSA
----------------	-----

Enclosure Rating	NEMA 1 Acier galvanisé
------------------	------------------------

Emballage

Poids de l'emballage (Kg)	1,601 kg
---------------------------	----------
