



## Principal

Product	Definite Purpose Starter
Ampere Rating	25 A
Horsepower Rating	2 hpà 115 V AC, monophasé 5 hpà 230 V AC, monophasé 10 hpà 230 V AC, 3 phases 15 hpà 460 V AC, 3 phases 20 hpà 575 V AC, 3 phases
Maximum Voltage Rating	600 V AC
Control Circuit Voltage	220 V AC at 50 Hz 208...240 V AC at 60 Hz
Phase	3 phases

## Complémentaire

Enclosure Rating	Not rated (open device)
Locked Rotor Amperes	150 Aà 230 V AC 125 Aà 460 V AC 100 Aà 575 V AC
Number of Poles	3P
Range	DPS
Overload Type	Melting alloy
Number of Thermal Units	3

## Emballage

Poids de l'emballage (Kg)	1,039 kg
---------------------------	----------

## Offre de la durabilité

Régulation REACH	<a href="#">Déclaration REACH</a>
Directive RoHS UE	Conforme <a href="#">Déclaration RoHS UE</a>
Sans mercure	Oui
Information sur les exemptions RoHS	<a href="#">Oui</a>
Régulation RoHS Chine	<a href="#">Déclaration RoHS pour la Chine</a> Produit en dehors du périmètre RoHS pour la Chine. Déclaration relative aux substances pour votre information.

## Garantie contractuelle

Garantie	18 months
----------	-----------