

8502SCO2V03

NEMA Contactor, Type S, nonreversing, Size 1, 27A, 10 HP at 575 VAC, 3 phase, up to 100 kA, 3 pole, 240 VAC coil, open



Principal

Product Type	Contacteur
Product Range	8502S
Contacteur Type	Non inverseur

Complémentaire

NEMA Size	1
Rated Current	27 A
Number of Poles	3P
Maximum Voltage Rating	600 V AC
Phase	3 phases
Horsepower Rating	7.5 HP at 200 V AC 7.5 HP at 230 V AC 10 HP at 460 V AC 10 HP at 575 V AC
SCCR	Disjoncteur 70 A maximum, SCCR: 100 kA at 480 V AC Fusible J 60 A maximum, SCCR: 100 kA at 600 V AC Fusible T 60 A maximum, SCCR: 100 kA at 600 V AC Fusible RK1 60 A maximum, SCCR: 100 kA at 600 V AC Fusible RK5 60 A maximum, SCCR: 100 kA at 600 V AC
Coil Voltage	240 V AC 60 Hz 220 V AC 50 Hz
Control Circuit Type	Common control circuit
Control Units	No control units
Pilot Light	Sans signalisation
Auxiliary Contacts	Sans
Other Equipment	Fusible non fourni
Terminal Type	Borniers à vis-étrier

Height	110,24 mm
Width	81,79 mm
Depth	107,19 mm

Environnemental

Enclosure Type	Not rated (open device)
Certifications	UL listed file E78351 CCN NLDX CSA

Emballage

Poids de l'emballage (Kg)	1,479 kg
Hauteur de l'emballage 1	11,430 cm
Largeur de l'emballage 1	14,986 cm
Longueur de l'emballage 1	20,320 cm

Offre de la durabilité

Régulation REACH	Déclaration REACH
Directive RoHS UE	Non conforme
Régulation RoHS Chine	Déclaration RoHS pour la Chine Produit en dehors du périmètre RoHS pour la Chine. Déclaration relative aux substances pour votre information.

Garantie contractuelle

Garantie	18 months
----------	-----------