

MCB 489 1P B 30A ACDC**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Product image**General ordering data**

Version	Miniature circuit breaker, Characteristic curve: B, Number of poles: 1, 30 A, white
Order No.	2477220000
Type	MCB 489 1P B 30A ACDC
GTIN (EAN)	4050118492774
Qty.	12 pièce(s)

MCB 489 1P B 30A ACDC

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Caractéristiques techniques

Dimensions and weights

Depth	60,2 mm	Depth (inches)	2,37 inch
Height	116 mm	Height (inches)	4,567 inch
Width	17,6 mm	Width (inches)	0,693 inch
Net weight	83,25 g		

Temperatures

Humidity	40 °C / 95 % rel. humidity, no condensation
----------	--

Electrical data

Voltage type	AC/DC	Rated AC voltage	277 V
Rated DC voltage	60 V	Rated current	30 A
Interrupting capacity	10 000 A		

General data

Characteristic curve	B	Number of poles	1
Version circuit breaker	Thermomagnetic	Typical lifetime in cycles mechanical	20 000
Typical lifetime in cycles electrical	6 000	Installation advice	DIN rail
Type of mounting	DIN rail	Type of fixing	Rail mounting
Vibration	according to IEC 60068-2-6	Shock	according to IEC 60068-2-27
Colour	white		

Classifications

ETIM 6.0	EC000042	ETIM 7.0	EC000042
ETIM 8.0	EC000042	ETIM 9.0	EC000042
ECLASS 9.0	27-14-19-01	ECLASS 9.1	27-14-19-01
ECLASS 10.0	27-14-19-01	ECLASS 11.0	27-14-19-01
ECLASS 12.0	27-14-19-01	ECLASS 13.0	27-14-19-01
ECLASS 14.0	27-14-19-01		

Downloads

Engineering Data	CAD data – STEP
Catalogues	Catalogues in PDF-format