



Principal

Product Type	Disjoncteur
Range	PowerPact M
Breaking Capacity Code	G
Trip Unit Technology	Électronique, basic, ET 1.0, LI

Complémentaire

Current Sensor Rating Range	350 A
Rated Current	350 A
Rated Operational Voltage	600 V AC
Mounting Mode	I-Line
Poles Description	3P
Breaking Capacity	65 kA à 240 V AC 35 kA at 480 V AC 18 kA à 600 V AC
Circuit Breaker Type	M-frame
Continuous Current Rating	80 %
Electrical Connection	I-Line connection ligne Cosses charge
Magnetic Tripping Current	700...3500 A
Terminal Identifier	AL800M23K
AWG Gauge	AWG 3/0...500 kcmil (aluminium / cuivre) pour 3 câble(s)
Tightening Torque	50 N.m pour 95...240 mm ² (AWG 3/0...500 kcmil)
Height	326,6 mm
Width	8,06 mm
Depth	210 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environnement

Certifications	CSA CEI Listé UL
----------------	------------------------

Emballage

Poids de l'emballage (Kg)	13,154 kg
---------------------------	-----------

Offre de la durabilité

Statut environnemental de l'offre	Produit Green Premium
Régulation REACH	Déclaration REACH
Directive RoHS UE	Conforme Déclaration RoHS UE
Sans mercure	Oui
Information sur les exemptions RoHS	Oui
Régulation RoHS Chine	Déclaration RoHS pour la Chine Produit en dehors du périmètre RoHS pour la Chine. Déclaration relative aux substances pour votre information.
Profil environnemental	Profil environnemental du Produit
Profil de circularité	Informations de fin de vie
Sans PVC	Oui

Garantie contractuelle

Garantie	18 months
----------	-----------