

INLINE GFCI CORD SETS

26020008-6



Excellent for industrial plant maintenance, equipment service, and construction site applications. Provides compliance with the National Electrical Code (NEC 2014) Article 590.6 for “Temporary Installations.” All inline models constructed with 20 AMP relays.

- For use on construction Sites and with industrial appliances
- Rainproof rated GFCI, UL listed for outdoor use.
- Custom cable gauges, lengths and terminations available by special order.
- Manual reset to prevent un-monitored equipment startup.
- Reset is required after GFCI trip or a power outage
- Add user-attachables to any cordset or tool to drive safety and code-compliance

SPECIFICATIONS

INLINE GFCI CORD SETS

PART#	GAUGE	WIRE TYPE	DESCRIPTION	AMP	LENGTH
26020002-6	14/3	SJTW	NEMA 5-15 P&R	15A	2 ft.
26020050-1	14/3	SJTW	NEMA 5-15 P&R	15A	50 ft.
26020124-2	14/3	SJTW	NEMA 5-15 P&R	15A	25 ft.
25080025-2	12/3	SJTW	NEMA 5-20 P&R	20A	25 ft.
26020011-6	12/3	SJTW	NEMA 5-15 P&R	15A	2 ft.
26020150-1	12/3	SJTW	NEMA 5-15 P&R	15A	50 ft.
26000011-6	12/3	SJTW	NEMA 6-20 P&R	20A/240V	2 ft.
44720013-2	10/3	SJTW	NEMA L6-30 P&R	240V/30A	6 ft.
44720065-4	10/3	SJTW	NEMA L6-30 P&R	240V/30A	15 ft.
TRI-SOURCE					
26020008-6	12/3	SJTW	NEMA 5-15P	15A	2 ft.
26020148-1	12/3	SJTW	NEMA 5-15P	15A	50 ft.
30040008-6	12/3	SEOW	NEMA 5-15P	15A	2.5 ft.

26020148-1



USER ATTACHABLES

PART#	GAUGE	DESCRIPTION	RELAY CAP.
25000016-6	18-12	120/240V	20A
30040006-6	16-12	High Capacity	20A