



Main

Range compatibility	Lexium 32
Accessory / separate part category	Communication accessories
Accessory / separate part type	Card
Product or component type	DeviceNet card
Product compatibility	Lexium 32M
Accessory / separate part destination	Servo drive

Complementary

Transmission rate	125 kbps 1640.42 ft (500 m) 500 kbps 328.08 ft (100 m) 250 kbps
Number of addresses	1...63
Web services	Inputs : polled, change of state, cyclic Standard assemblies Extended assemblies Outputs : polled Motion assemblies Communication monitoring CIP motion profile Auto device replacement
Communication port protocol	DeviceNet
Electrical connection	1 connector 1 removable 5-way screw connector 5
Local signalling	MS (Module Status) 1 LED green/red Control mode received, reference received 1 graphic display terminal NS (Network Status) 1 LED

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	2.01 oz (57 g)

Package 1 Height	1.65 in (4.2 cm)
Package 1 width	2.44 in (6.2 cm)
Package 1 Length	3.54 in (9 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------