


Industrial grade straight blade receptacles

Product description

2-pole, 3-wire grounding
15A, 125V/AC;
20A, 125V/AC
NEMA 5-15R, 5-20R



5-15R

5-20R

Special use panel-mount industrial single receptacles



Rating A	V/AC	NEMA	Description	Color	Catalog no.		
15	125	5-15R	Brown, strap center-center spacing 1.9375" (49.2mm), back & side wire, short strap	B	□ 5284B		

Corrosion resistant premium industrial grade receptacles



Rating A	V/AC	NEMA	Description	Color suffix	Catalog no.		
15	125	5-15R	Premium corrosion resistant duplex receptacle, back & side wire	GY, Y	□ AH5262CR__		
20	125	5-20R	Premium corrosion resistant duplex receptacle, back & side wire	GY, Y	□ AH5362CR__		

Watertight special use industrial grade receptacles



Rating A	V/AC	NEMA	Description	Color	Catalog no.		
15	125	5-15R	Single watertight receptacle, back wire	Y	□ 60W47		
			Single watertight receptacle, back wire	BK	□ 60W47BK		
			Duplex watertight receptacle, back wire	Y	□ 60W47DPLX		
			Duplex watertight receptacle, back wire	BK	□ 60W47DPLXBK		
20	125	5-20R	Single watertight receptacle, back wire	Y	□ 60W33		
			Single watertight receptacle, back wire	BK	□ 60W33BK		
			Duplex watertight receptacle, back wire	Y	□ 60W33DPLX		
			Duplex watertight receptacle, back wire	BK	□ 60W33DPLXBK		

NOTE: See Complex Environment (Section D) for more information

Accessories for industrial grade NEMA 6-15 & 6-20 receptacles


Description	Catalog no.		
1-Gang, cast aluminum outlet box, 3 hole 0.75" (19.05mm)	□ 1116		



1116

Color ordering information:

For ordering devices, include Catalog no. followed by the Color suffix: B (Brown), BK (Black), GY (Gray), Y (Yellow)



Specification information: Panel mount industrial receptacles: A-31, Corrosion resistant premium industrial receptacles: A-35, Watertight receptacles: A-35

Compliances, specifications and availability are subject to change without notice.

Build-to-spec customizable devices - Page A-6

Indicates NAFTA compliant - Page Q-32

RoHS compliant - Page Q-32