



### Main

Range of Product	Modicon Momentum automation platform
Product or Component Type	Interbus communication adaptor
Communication port protocol	Interbus generation SUP1 3
Method of access	Master/Slave Continuous shift register
Transmission Rate	500 kbit/s
Transmission support medium	Twisted pair

### Complementary

Topology	Ring
Number of devices per segment	0...254
Maximum cable distance between devices	41994.75 Ft (12800 m) 1312.34 ft (400 m) between two modules
Fail state	Fail safe
Control parameter	CRC-16
Supply	From I/O base
Marking	CE
Local signalling	For bus enable (BA) 1 LED For remote bus check (RC) 1 LED For remote bus disabled (RD) 1 LED For logic power check (UL) 1 LED
Electrical connection	2 connectors SUB-D 9 for connecting Interbus
Module format	Standard
Net Weight	0.15 lb(US) (0.07 kg)

### Environment

Product Certifications	FM Class 1 Division 2[RETURN]CSA[RETURN]UL
IP Degree of Protection	IP20
Protective treatment	TC
Resistance to electrostatic discharge	4 KV contact IEC 801-2 8 kV on air IEC 801-2
Resistance to electromagnetic fields	9.14 V/m (10 V/m) 80...1000 MHz IEC 801-3
Ambient Air Temperature for Operation	32...140 °F (0...60 °C)
Ambient Air Temperature for Storage	-40...185 °F (-40...85 °C)
Relative Humidity	95 % without condensation
Operating altitude	<= 16404.2 ft (5000 m)

### Ordering and shipping details

Category	18206-MOMENTUM PROCESSORS,I/O BASES,CONN.
Discount Schedule	PC31
GTIN	3595862060721
Returnability	Yes
Country of origin	FR

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.17 in (5.500 cm)
Package 1 Width	7.13 in (18.100 cm)
Package 1 Length	10.24 in (26.000 cm)
Package 1 Weight	6.88 oz (195.000 g)
Unit Type of Package 2	S03
Number of Units in Package 2	8
Package 2 Height	11.81 in (30.000 cm)
Package 2 Width	11.81 in (30.000 cm)
Package 2 Length	15.75 in (40.000 cm)
Package 2 Weight	4.52 lb(US) (2.048 kg)

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

## Contractual warranty

Warranty	18 months
----------	-----------