


# GS1AN11

Auxiliary contacts, TeSys GS, 1NC+1NO, instantaneous, left side mounting, for GS1 and GS2 with front/right handle



## Main

Range of Product	TeSys
Device short name	GS1AN
Product or Component Type	Auxiliary contact
Contact application	O and I position signalling
Contacts type and composition	1 NC + 1 NO
Contact operation	Instantaneous
[I <sub>th</sub> ] conventional free air thermal current	20 A (at 104 °F (40 °C))
[I <sub>e</sub> ] rated operational current	1 A 220 V DC-13 10 A 230 V AC-15 12 A 127 V AC-15 4 A 48 V DC-13 6 A 440 V AC-15 8 A 400/415 V AC-15 1.2 A 110 V DC-13

## Complementary

Range compatibility	TeSys TeSys GS switch-disconnector-fuse
Mechanical durability	30000 cycles
Electrical durability	30000 cycles AC-15
Switch rated current	1250 A 160 A 400 A 50 A 63 A 800 A 250 A 315 A 600 A 125 A 100 A 60 A 200 A 630 A
Fuse type	NFC DIN BS
Type of operating handle	Direct frontal Direct right side External right side External frontal
Net Weight	0.29 lb(US) (0.132 kg)

## Ordering and shipping details

Category	22640-IEC DISCONNECT-GS1,LK3
Discount Schedule	I11
GTIN	3389110563276
Returnability	No
Country of origin	FR

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.18 in (3.0 cm)
Package 1 Width	2.76 in (7.0 cm)
Package 1 Length	5.12 in (13.0 cm)
Package 1 Weight	4.44 oz (126.0 g)
Unit Type of Package 2	S01
Number of Units in Package 2	20
Package 2 Height	5.91 in (15.0 cm)
Package 2 Width	5.91 in (15.0 cm)
Package 2 Length	15.75 in (40.0 cm)
Package 2 Weight	5.96 lb(US) (2.704 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Styrene, which is known to the State of California to cause cancer. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>

## Contractual warranty

Warranty	18 months
----------	-----------