



**KNIPEX CoBolt® Compact Bolt Cutter**  
DIN ISO 5743




71 01 200   
black atramentised pliers, plastic-coated handles




71 02 200   
black atramentised pliers, handles with slim multi-component covers




71 12 200   
black atramentised pliers, handles with slim multi-component covers



71 21 200   
black atramentised pliers, plastic-coated handles  
Style 2: 20° angled head with single-sided joint bar and diagonal cutting edge for flush cutting; with space for gripping



71 22 200   
black atramentised pliers, handles with slim multi-component covers  
Style 2: 20° angled head with single-sided joint bar and diagonal cutting edge for flush cutting; with space for gripping



71 31 200

black atramentised pliers, plastic-coated handles, with recess for easier cutting of thicker wires  
 Style 3:the recess in the blade allows easier cutting of thicker wires, e. g. for false ceilings



71 32 200

black atramentised pliers, handles with slim multi-component covers, with recess for easier cutting of thicker wires  
 Style 3:the recess in the blade allows easier cutting of thicker wires, e. g. for false ceilings



71 41 200

black atramentised pliers, plastic-coated handles, with recess for easier cutting of thicker wires  
 Style 4:the recess in the blade allows easier cutting of thicker wires, e. g. for false ceilings, 20° angled head with single-sided joint bar and diagonal cutting edge for flush cutting; with space for gripping



- Description
- Special
- induction hardened edges cut hard, soft and piano wire
- cuts material like bolts, nails, rivets, etc. up to 5.2 mm dia.
- exceptional cutting performance with minimum effort because of new lever action design
- cutting edge hardness approx. 64 HRC
- Chrome vanadium heavy-duty steel; forged, oil-hardened

**60 % less effort required compared to conventional high-leverage diagonal cutters**

The ingenious lever-action mechanism ensures an extremely favourable lever ratio with very little friction. The cutting force is about 20 times higher than the hand force applied.

| Product Number | EAN<br>4003773- | Style | Ø mm | Ø mm | Ø mm | Ø mm | mm  | g   |
|----------------|-----------------|-------|------|------|------|------|-----|-----|
| 71 01 200      | 033165          | 0     | 6,0  | 5,20 | 4,00 | 3,60 | 200 | 335 |
| 71 02 200      | 047056          | 0     | 6,0  | 5,20 | 4,00 | 3,60 | 200 | 372 |

|           |        |   |     |      |      |      |     |     |
|-----------|--------|---|-----|------|------|------|-----|-----|
| 71 12 200 | 066859 | 1 | 6,0 | 5,20 | 4,00 | 3,60 | 200 | 375 |
| 71 21 200 | 066866 | 2 | 6,0 | 5,20 | 4,00 | 3,60 | 200 | 320 |
| 71 22 200 | 066873 | 2 | 6,0 | 5,20 | 4,00 | 3,60 | 200 | 375 |
| 71 31 200 | 042327 | 3 | 6,0 | 5,20 | 4,00 | 3,60 | 200 | 330 |
| 71 32 200 | 066880 | 3 | 6,0 | 5,20 | 4,00 | 3,60 | 200 | 370 |
| 71 41 200 | 066897 | 4 | 6,0 | 5,20 | 4,00 | 3,60 | 200 | 335 |

technical change and errors excepted