

OHY Hybrid Convection and Forced-Air Wall Heater



Surface with Trim Sleeve

Surface

Recessed



VERSION AVAILABLE



Training available online www.ouellet.com

Features

Color

- Standard: white, almond.
- Optional: metallic silver, bronze, metallic charcoal, textured black, beige-grey, aluminum, semi-gloss black (10% upcharge).
- Custom colors available upon request.

Finish

- Standard: epoxy/polyester powder paint.

Voltage

- 120V, 240V, 1-phase.

Construction

- Cast aluminum front cover.
- Steel bar grilles prevent the insertion of foreign objects; smooth-finish paint is washable and anti-yellowing.
- Automatic reset safety device.
- Built-in white LED night light. **1**

Fan

- Whisper-quiet squirrel-cage fan.
- Factory-lubricated motor.

Heating element

- Nichrome element provide instant heat.

Control

- Built-in electronic digital thermostat/timer. **2**
- Thermostat mode: pulse modulation: automatic convection to fan-forced switch-over at 1000W.
- Timer mode: 5-30 minutes full power fan-forced boost. **3**

Installation

- 4 in. (102 mm) minimum clearance to floor.
- May be recessed or surface-mounted with or without casted trim sleeve in 2 in. X 3 in. stud partitions.
- Mounting holes for ease of installation.
- Large wiring compartment.

Warranty

- 2-year warranty against defects.
- 5-year warranty on the heating element.

Application

- Bathroom, kitchen, family room, entrance way.

Models

Watts	Volts	Product #	Weight	
			lb	kg
1500	120	OHY1502	22.75	10.3
2000 ¹	240	OHY2000 ¹	22.75	10.3

Options

Product #	Description
OHY-CM	Aluminum casted trim sleeve
OHY-DIS ²	Disconnect switch, 20A at 250V

¹BEWARE: Not available for 208V.

² Factory installed or kit.

Add "BL" for white, "AM" for almond.

Optional colors shown in the color chart section (page 105) are available with a 10% upcharge.

For the options available as factory installed and kit, if not mentioned on the order, will automatically be shipped as a kit.

