

Rittal – The System.

Faster – better – everywhere.

Baying systems TS 8 double – TS 8901.290

Date : Aug 5, 2016

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Baying systems TS 8 double – TS 8901.290

: 05.08.2016 build on www.rittal.com/ca-en



Product description

Material:	Enclosure frame: Carbon steel, 1.5 mm Roof: Carbon steel, 1.5 mm Door: Carbon steel, 2.0 mm Rear panel: Carbon steel, 1.5 mm Base plates: Carbon steel, 1.5 mm Mounting plate: Carbon steel, 3.0 mm
Surface finish:	Enclosure frame: Dipcoat-primed Door, roof and rear panel: Dipcoat-primed, powder-coated on the outside, textured paint Mounting plate and base plates: Zinc-plated
Color:	RAL 7035
Protection category IP to IEC 60 529:	IP 55
Protection category NEMA:	NEMA 12
Supply includes:	Enclosure frame with door(s) Roof plate Rear panel, detachable 4 eyebolts Lock: 3 mm double-bit Base Plates Mounting plate
Packaging unit:	1 pc(s).
EAN:	38121

Product features

Dimensions:	Height: 2000 mm (79 ") Width: 1600 mm (63 ") Depth: 500 mm (20 ")
--------------------	---

Number of doors:	2
-------------------------	---





Weight/pack:	245.3 kg
---------------------	----------

Approvals

Approvals:	<ul style="list-style-type: none"> Bureau Veritas (EN) CSA (EN) Germanischer Lloyd (EN) Lloyds Register of Shipping Norske Veritas (EN) Russian Maritime Register of Shipping (EN) TUV EN UL + C-UL (EN)
-------------------	---

Downloads

Data sheets:	Graphics (US)
---------------------	---------------

Documentation:	<ul style="list-style-type: none"> Further information (EN, US) Instructions FR, EN, DE Load brochure EN, DE PE conductor brochure EN, DE
-----------------------	---

CAD drawings:	Request
----------------------	---------
