



Main

Range of product	Multi9
Product or Component Type	Shunt trip release with OC contact
Device short name	MX + OF
Signal contacts composition	1 C/O
Line Rated Current	3 A at 415 V, AC 6 A at <= 240 V, AC
[Uc] control circuit voltage	110...415 V AC 50/60 Hz 110...130 V DC
9 mm pitches	2

Complementary

Range compatibility	Multi 9 Multi9 C60 C60BP Multi 9 Multi9 C60 C60BPR Multi 9 Multi9 C60 C60SP Multi 9 Multi9 GFP GFP Multi 9 Multi9 C60H-DC C60H-DC
Local signalling	Action indicator
Mounting Mode	Fixed
Mounting Support	DIN rail
Comb busbar and distribution block compatibility	Top YES
Height	3.25 in (82.5 mm)
Width	0.71 in (18 mm)
Depth	2.68 in (68 mm)
Net Weight	0.14 lb(US) (0.065 kg)
Connections - terminals	Clamp terminal bottom) - 1 0.00 in ² (2.5 mm ²) AWG 14) - rigid Clamp terminal bottom) - 2 0.00 in ² (1.5 mm ²) AWG 16) - rigid
Wire stripping length	0.35 in (9 mm) for bottom connection
Tightening torque	8.85 lbf.in (1 N.m) bottom

Environment

Standards	EN/IEC 60947-1
Product Certifications	CCC[RETURN]UL[RETURN]PCT[RETURN]UR
Pollution degree	3
Ambient Air Temperature for Operation	-13...122 °F (-25...50 °C)
Ambient Air Temperature for Storage	-40...185 °F (-40...85 °C)

Ordering and shipping details

Category	00948-M9 GEN 2 CB UL1077 / IEC
Discount Schedule	DE2
GTIN	3606480639074
Returnability	Yes
Country of origin	BE

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.18 in (3.000 cm)
Package 1 Width	3.07 in (7.800 cm)
Package 1 Length	3.70 in (9.400 cm)
Package 1 Weight	2.50 oz (70.900 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	8
Package 2 Height	3.35 in (8.500 cm)
Package 2 Width	3.94 in (10.000 cm)
Package 2 Length	10.43 in (26.500 cm)
Package 2 Weight	22.33 oz (633.000 g)
Unit Type of Package 3	S03
Number of Units in Package 3	32
Package 3 Height	11.81 in (30.000 cm)
Package 3 Width	11.81 in (30.000 cm)
Package 3 Length	15.75 in (40.000 cm)
Package 3 Weight	6.46 lb(US) (2.932 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.