

LED replacement lamps



Reflector Lamps

Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (In)	Lumens Initial	CBCP	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Dimmable	ENERGY STAR® Status	#Location Rating	Additional Information	
R20																		
	MED	7	38268	LED7DR20/827	120	6	3.64	470		2700	80	45W	25,000	Yes		Damp	White	
			43233	LED7DR20/830	120	6	3.64	470		3000	80	45W	25,000	Yes		Damp	White	
			38273	LED7DR20/850	120	6	3.64	500		5000	80	45W	25,000	Yes		Damp	White	
BR30																		
	MED	10	68160	LED10DR303/827W	120	6	5.4	700		2700	80	65W	25,000	Yes	★	Damp	Frosted, White body	
			68161	LED10DR303/830W	120	6	5.4	700		3000	80	65W	25,000	Yes	★	Damp	Frosted, White body	
			69107	LED10DR303/850W	120	6	5.4	700		5000	80	65W	25,000	Yes	★	Damp	Frosted, White body	
			43234	LED10DR30V/827W	120	3	5.37	650		2700	80	65W	15,000	Yes		Damp	Frosted, White body	
			43237	LED10DR30V/830W	120	3	5.37	650		3000	80	65W	15,000	Yes		Damp	Frosted, White body	
BR40																		
	MED	13	64176	LED13DBR40/827	120	6	6.3	1070		2700	80	85W	25,000	Yes	★	Damp	Frosted, White body	
			14708	LED13DBR40/830	120	6	6.3	1070		3000	80	85W	25,000	Yes	★	Damp	Frosted, White body	
			69108	LED13BR40/850	120	3	6.34	1070		5000	80	85W	25,000	Yes	★	Damp	Frosted, White body	

Directional Lamps (MR16 - GU10)

Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (In)	Lumens Initial	CBCP	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Dimmable	ENERGY STAR® Status	#Location Rating	Additional Information	
12 Volt AC/DC MR16																		
	GU5.3	6.5	75155	LED6.5XDMR16W82715	12	6	1.87	500	4900	2700	80	50W	25,000	Yes	★	Damp	Spot 15° beam, White	
			75153	LED6.5DMR16W83015	12	6	1.87	520	4900	3000	80	50W	25,000	Yes	★	Damp	Spot 15° beam, White	
			75158	LED6.5DMR16W84015	12	6	1.87	550	5000	4000	80	50W	25,000	Yes	★	Damp	Spot 15° beam, White	
			93226	LED6.5DMR16W82725	12	6	1.79	500	2350	2700	80	50W	25,000	Yes	★	Damp	Narrow 25° beam, White	
			93222	LED6.5DMR16W83025	12	6	1.79	520	2350	3000	80	50W	25,000	Yes	★	Damp	Narrow 25° beam, White	
			93228	LED6.5DMR16W84025	12	6	1.79	550	2400	4000	82	50W	25,000	Yes	★	Damp	Narrow 25° beam, White	
			93227	LED6.5DMR16W82735	12	6	1.79	500	1350	2700	80	50W	25,000	Yes	★	Damp	Flood, 35° beam, White	
			93223	LED6.5DMR16W83035	12	6	1.79	520	1350	3000	80	50W	25,000	Yes	★	Damp	Flood, 35° beam, White	
			93229	LED6.5DMR16W84035	12	6	1.79	550	1400	4000	80	50W	25,000	Yes	★	Damp	Flood, 35° beam, White	
			7	21359	LED7MRX16R930/10	12	6	2.01	350	8000	3000	95	50W	25,000	-		Damp	Spot, 10° beam, Reveal
93412	LED7DMR16S830/15	12	6	2.3	460	3800	3000	80	35W	25,000	Yes		Damp	Spot 15° beam, Silver				
Value 12 Volt AC/DC MR16																		
	GU5.3	4.5	34560	LED4.5DMR1682735	12	6	1.78	380	1000	2700	80	35W	25,000	Yes	★	Dry	Flood, 35° beam, White	
			34561	LED4.5DMR1683035	12	6	1.78	400	1000	3000	80	35W	25,000	Yes	★	Dry	Flood, 35° beam, White	
			34563	LED4.5DMR1684035	12	6	1.78	400	1100	4000	80	35W	25,000	Yes	★	Dry	Flood, 35° beam, White	
			6.5	34606	LED6.5DMR1682725	12	6	1.78	500	2350	2700	80	50W	25,000	Yes	★	Dry	Narrow 25° beam, White
			34607	LED6.5DMR1682735	12	6	1.78	500	1350	2700	80	50W	25,000	Yes	★	Dry	Flood, 35° beam, White	
			34611	LED6.5DMR1683025	12	6	1.78	530	2350	3000	80	50W	25,000	Yes	★	Dry	Narrow 25° beam, White	
34625	LED6.5DMR1683035	12	6	1.78	530	1350	3000	80	50W	25,000	Yes	★	Dry	Flood, 35° beam, White				
120 Volt GU10																		
	MR16	GU10	3.5	37114	LED4D/GU1083035	120	6	2.1	300	550	3000	80	35W	25,000	Yes	★	Dry	Flood, 35° beam, White
			4	89020	LED4D/GU10/NFLTP	120	3	2.1	250	720	3000	80	35W	25,000	Yes	★	Damp	Flood, 35° beam, White
			6	26346	LED6D/GU10/NFL/TP	120	3	2.1	430	1100	3000	80	50W	25,000	Yes	★	Damp	Flood, 35° beam, White

Updated / New Product

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and Current makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

** Minimum order quantity = 6

★ ENERGY STAR® status: ENERGY STAR® certified. Lamps without a ★ are not ENERGY STAR® certified.

UL 1993 Environmental Requirements for LED LAMPS

Location, damp – Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry – Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet – Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

Notes: 1) Product descriptions ending in "/TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

Get more information at

www.gecurrent.com