

CP POST CONNECTOR



- Manufactured from high conductivity copper alloy.
- Compact design saves space and reduces installation time.
- Range Taking for reduced inventories and flexibility.
- Re-Usable.
- CP-8, CP-4, CP-0, and CP-250 are UL Listed and cUL certified to UL467
- Suitable for use in circuits rated 35KV or less; proper high voltage spacing and insulation techniques must be used.
- CP-500 and CP-1000 are NOT CSA Certified.
- For Copper Conductor only.
- UL File E6207
- UL 486A/B

Item ID	Conductor Range	Bolt/Stud Size	Length	Width	Height	Hex Size	Standard Package Quantity	NAED/UPC Number
CP-8	8-14 AWG	#10	0.8180	0.3950	0.4500	S	100	0783669029956
CP-4	4-14 AWG	1/4	1.0920	0.5400	0.5900	S	100	0783669030051
CP-0	1/0-8 AWG	5/16	1.5000	0.7300	0.7630	1/4	50	0783669030105
CP-250	250 kcmil-6 AWG	3/8	1.9688	0.9375	1.0625	1/4	25	0783669030150
CP-500	500 kcmil-4/0 AWG	1/2	3.0000	1.4060	1.4690	3/8	6	0783669030174
CP-1000	1000 kcmil-500 kcmil	1/2	3.9688	2.0000	2.1560	1/2	3	0783669030198