

Product data sheet

Characteristics

QMB3IMA12

Surge protection device, Surgelogic, QMB, 120kA, 120/240 VAC, 3 phase, 4 wire, SPD type 2



Main

Product	Surge protection device
Range	Surgelogic
Device Short Name	IMA

Complementary

Voltage Rating	120/240 V AC
MCOV	150 V
SCCR	200 kA
Surge Current	120 kA
Nominal Discharge Current	20 kA
Number of Phases	3 phase
Wiring Configuration	4-wire
Connection	Plug in
Local Signalling	Alarm fault Status LED
Provided Equipment	Alarm enable/disable switch Surge counter Dry contacts
Height	8.90 in (226 mm)
Width	22.99 in (584 mm)
Depth	6.50 in (165 mm)

Environment

Enclosure Material	Painted sheet steel
Standards	UL 1449:ed. 3 CSA C22.2 No 8:1986 UL 1283 UL 67 CSA C22.2 No 29

Ordering and shipping details

Category	08251-TVSS UNIT
Discount Schedule	PE1A
GTIN	3606486148426
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.90 in (22.6 cm)
Package 1 Width	22.99 in (58.4 cm)
Package 1 Length	6.50 in (16.5 cm)
Package 1 Weight	40.00 lb(US) (18.144 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Under investigation

Contractual warranty

Warranty	18 months
----------	-----------