



Main

| | |
|--------------|--------------------------------|
| Product Type | Industrial Control Transformer |
| Type | T |

Complementary

| | |
|--------------------------------|--|
| Number of Phases | 1 phase |
| Power Rating | 2000 VA UL 2000 VA CSA 2000 VA NOM 1500 VA CE |
| Primary to Secondary Voltage | 208 V 120 V |
| Temperature Rise | 115 °C |
| Electrical Connection | Screw clamp terminals |
| Height | 6.17 in (156.72 mm) |
| Width | 7.06 in (179.32 mm) |
| Depth | 7.17 in (182.12 mm) |
| Material | Copper: winding |
| Fingersafe Cover Compatibility | FSC2 |

Environment

| | |
|------------------------|--|
| Certifications | CSA file LR37055 guide 184-N-90[RETURN]UL listed file E61239 |
| Enclosure Type | Not rated (open device) |
| Insulation Temperature | 356 °F (180 °C) |

Ordering and shipping details

| | |
|-------------------|---------------------------|
| Category | 16206-9070 T (NOT TF) MTO |
| Discount Schedule | CP8 |
| GTIN | 785901322238 |
| Returnability | Yes |
| Country of origin | US |

Packing Units

| | |
|------------------------------|--------------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 11.80 in (29.972 cm) |
| Package 1 Width | 12.00 in (30.48 cm) |
| Package 1 Length | 14.80 in (37.592 cm) |
| Package 1 Weight | 46.10 lb(US) (20.911 kg) |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant with Exemptions |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |
| PVC free | Yes |

Contractual warranty

| | |
|----------|----------|
| Warranty | 10 Years |
|----------|----------|