



Main

Range of product	OsiSense XG
Product or component type	Electronic tag
RFID electronic tag name	XGHB
RFID frequency	13.56 MHz
Design	Flat form 40 x 40 x 15
Memory capacity	3.408 kB
Associated smart antenna	XGCS
[Sn] nominal sensing distance	1.30 in (33 mm) XGCS49 1.89 in (48 mm) XGCS89 1.89 in (48 mm) XGCS85
Outer dimension	40 x 40 x 15 mm
Quantity per set	Set of 1
Read time	$9.25 + 0.375 \times (\text{number of 16-bit words})$ ms
Write time	$13 + 0.8 \times (\text{number of 16-bit words})$ ms
IP degree of protection	IP68
Fixing mode	By screws By clips

Complementary

Memory type	EEPROM
Memory operation	Read/write
Number of read cycles	Unlimited
Number of write cycles	100000 -13...158 °F (-25...70 °C) 2500000 86 °F (30 °C)
Maximum linear speed with "auto read/write function"	10.17 ft/s (3.1 m/s) XGCS49 read a serial number) 4.59 ft/s (1.4 m/s) XGCS49 read a word) 8.86 ft/s (2.7 m/s) XGCS89 read a word) 8.86 ft/s (2.7 m/s) XGCS85 read a word) 3.94 ft/s (1.2 m/s) XGCS49 read or write 10 words)

15.75 ft/s (4.8 m/s) XGCS89 read a serial number)
 5.91 ft/s (1.8 m/s) XGCS89 read or write 10 words)
 15.75 ft/s (4.8 m/s) XGCS85 read a serial number)
 5.91 ft/s (1.8 m/s) XGCS85 read or write 10 words)

Data retention time	10 year(s)
Mounting location	Possible on metal support
Material	PBT (polybutylene terephthalate)
Net weight	0.07 lb(US) (0.031 kg)

Environment

Standards	ISO 14443
Ambient air temperature for operation	-13...158 °F (-25...70 °C)
Ambient air temperature for storage	-40...185 °F (-40...85 °C)
Vibration resistance	2 mm 5...29.5 Hz)EN 60068-2-6 7 gn 29.5...150 Hz)EN 60068-2-6
Shock resistance	30 gn 11 ms EN 60068-2-27
IK degree of protection	IK02 EN 50102

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.34 oz (38 g)
Package 1 Height	3.54 in (9 cm)
Package 1 width	0.79 in (2 cm)
Package 1 Length	2.36 in (6 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Contractual warranty

Warranty	18 months
----------	-----------