



**GREENLEE.**  
A Textron Company

MADE FOR THE TRADE!™

SPEED PUNCH LOCK (POP) (SP-LOCK)

SPEED LOCK, SPEED PUNCH™ System



Image  
Unavailable

Cat No: 52047817

UPC No: 783310092773

### Description

---

- SPEED PUNCH® saves time and money with every hole.
- Up to 3X's faster setup and disassembly.
- No-Thread punch design eliminates cross-threading.
- Available in 3/4" - 2" conduit sizes and punch kits

### Specifications

---

- Application : For punching conduit sized holes in mild steel, aluminum, fiberglass, and plastic.
- Capacity : Mild steel up through 10 gauge (3.5 mm).
- Draw Studs : Std. Draw Stud: 7212SP11 (3/4" x 4.77") Long Draw Stud: 7212SP12 (3/4" x 5.63") - For USE W/746 HYDRAULIC RAM.
- Driver : Use with Greenlee Hydraulic Drivers - Quick Draw® Flex (7704SB), Quick Draw® Standard (7804SB), QUICK DRAW 90® (7904SB) AND HYDRAULIC RAM (746 W/7212SP12 LONG DRAW STUD), OR LS50 BATTERY-POWERED DRIVER (LS50L11A).
- Material : Carbon Steel, Black Oxide Coated
- Operation : Must be used with other SPEED PUNCH® System components.
- Size : 1.75" Dia. x 1.63"
- Sub Brand : SPEED PUNCH®#174
- Type : Knockout Punches
- Weight : 0.45 lbs. (0.22 kg)