

Product data sheet

Characteristics

8903SVH2V02

Contactor, Type S, multipole lighting,
electrically held, 200A, 3 pole, 110/120 VAC
50/60 Hz coil, NEMA 3R



Main

Product	Electrically Held Lighting Contactor
Type	S

Complementary

Control Circuit Voltage	120 V AC 60 Hz 110 V AC 50 Hz
Current Rating	200 A
Number of Poles	3P
Control Units	No control units
Pilot Light	Without pilot light
Auxiliary Contacts	Without
Other Options	None
Electrical connection	Lugs
Height	40.31 in (1024 mm)
Depth	9.13 in (232 mm)
Maximum Width	12.83 in (326 mm)

Environment

Enclosure Type	NEMA 3R Stainless Steel surface none
Product certifications	UL Listed CSA

Ordering and shipping details

Category	21325 - 8903 S (NOT S°C) ELECT.
Discount Schedule	CP1
GTIN	00785901024088
Nbr. of units in pkg.	1
Package weight(Lbs)	9.75 lb(US) (4.42 kg)
Returnability	No
Country of origin	MX

Offer Sustainability

California proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty

18 months
