

# AF2316G12S

Adaptor, I-Line Busway, max 1600A rated, aluminum, slot connection, 3 wire, mounted indoors



## Main

Product	Adaptor
Range	I-Line

## Complementary

Rated Current	1600 A aluminium
Rated Operational Voltage	600 V AC/DC 50/60 Hz
Length	12 in (304.80 mm)
Material	Aluminium: busbar
I-LINE Value End	Slot
Number of Phases	3 phase
For Use with	Busbar trunking 1600 A aluminium
Protection Type	50 percent capacity integral ground bus
Wiring Configuration	3-wire
Mounting Location	Indoor

## Environment

Standards	UL 857 CSA C22.2 No 27:1994 IEC 61439-6
-----------	---

## Ordering and shipping details

Category	20260-AF2/AFH2 1600A 3WIRE-COMM
Discount Schedule	PE8
GTIN	785901016700
Returnability	Yes
Country of origin	US

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	25.00 lb(US) (11.34 kg)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations
PVC free	Yes

## Contractual warranty

Warranty	18 months
----------	-----------