

Main

Product or Component Type	Single Throw Safety Switch
Disconnecter device type	Fusible disconnect
Number of poles	3
Electrical Connection	Lugs
Series name	Heavy duty

Complementary

Line Rated Current	400 A
Device Composition	None
Device mounting	Surface
[Ue] rated operational voltage	600 V AC/DC
Maximum Horse Power Rating	100 Hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 250 Hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 125 Hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 350 Hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 50 Hp 250 V at DC 50 hp 600 V at DC
AWG gauge	AWG 1/0...750 kcmil copper or aluminium
Tightening torque	550 lbf.in (62.14 N.m) (AWG 1/0...750 kcmil)
Height	46.25 in (1174.75 mm)
Width	26.25 in (666.75 mm)
Depth	10.13 in (257.30 mm)

Environment

Product Certifications	CSA
NEMA degree of protection	NEMA 3R/12 galvanized steel

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.