



Main

Range of Product	Homeline
Product or Component Type	Load Center
Line Rated Current	125 A
[Ue] rated operational voltage	120/240 V AC
Mounting Mode	Wall mount
Short-circuit current	10 kA

Complementary

AWG gauge	AWG 6...AWG 2/0 aluminium/copper
Load center type	Main lugs
Number of spaces	30
Number of circuits	60
Number of tandem circuit breakers	30
Phase	1 phase
Cover type	Combination flush/surface cover
Device Composition	Grounding bar included (not installed)
Wiring configuration	3-wire
Material	Tin plated aluminium: busbar
Enclosure Material	Welded sheet steel
Cover colour	White
Box number	10

Environment

Product Certifications	CSA
NEMA degree of protection	NEMA 1 indoor)
Ambient Air Temperature for Operation	23 °F (-5 °C) 104 °F (40 °C)

Ordering and shipping details

Category	00199-DE5 MISC. SERVICE PARTS
Discount Schedule	DE5
GTIN	785901226550
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.70 in (14.478 cm)
Package 1 Width	16.10 in (40.894 cm)
Package 1 Length	36.50 in (92.71 cm)
Package 1 Weight	29.92 lb(US) (13.572 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations