



Main

Range	Spacial
Product or Component Type	Drive flush mounting kit
Accessory category	Mounting and fixing accessory
Product Specific Application	Process and utilities
Range compatibility	Altivar variable speed drive ATV630[RETURN]Altivar variable speed drive ATV930[RETURN]Spacial SF and SM enclosures[RETURN]Altivar variable speed drive ATV340
Compatibility for Altivar Process 630-930, size:	5
Motor power kW	30 KW 220/240 V 37 KW 220/240 V 45 KW 220/240 V 55 KW 380/480 V 75 KW 380/480 V 90 kW 380/480 V
Mounting location	1 back of enclosure mounting plate 2 inside enclosure
Kit composition	1 x mounting plate with flanges and integrated gasket, steel with anti-corrosive coating by screws and nuts 1 x fixing accessories 1 x drilling template 1 x instruction sheet 1 x edge protector profile, plastic 1 x fan support 1 x cover for fan protection

Complementary

Permanent permissible load	128.97 lb(US) (58.5 kg)
Color	Gray RAL 7035)
Height	External 38.39 in (975 mm) Cut-out 36.22 in (920 mm)
Width	Cut-out 14.96 in (380 mm) External 16.81 in (427 mm)
Depth	Wall-enclosure separation 8.09 in (205.5 mm)
Net Weight	24.44 lb(US) (11.086 kg)
Services	Configuration of enclosure pre-drilled back Factory installation drive flush mounting kit

Environment

IP degree of protection	IP55 conforming to IEC 60529
-------------------------	------------------------------

Ordering and shipping details

Category	22277-ATV930 FRAMES 3 & 4
Discount Schedule	CP4E
GTIN	3606485442488
Returnability	Yes
Country of origin	FR

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.91 in (15.0 cm)
Package 1 Width	17.72 in (45.0 cm)
Package 1 Length	39.76 in (101.0 cm)
Package 1 Weight	24.44 lb(US) (11.086 kg)
Unit Type of Package 2	PAM
Number of Units in Package 2	20
Package 2 Height	65.35 in (166.0 cm)
Package 2 Width	39.37 in (100.0 cm)
Package 2 Length	47.24 in (120.0 cm)
Package 2 Weight	518.09 lb(US) (235.0 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations