



Main

Range	TeSys
Product name	TeSys LK
Product or Component Type	Disconnect Switch
Disconnecter device type	Non-fusible disconnect switch
Suitability for isolation	Yes

Complementary

Poles description	3P
Network type	AC
Network Frequency	50/60 Hz
[Ie] rated operational current	800 A400 V AC AC-22A IEC 800 A400 V AC AC-23A IEC 630 A690 V AC AC-22A IEC 400 A690 V AC AC-23A IEC 800 A CSA 800 A UL
[Ue] rated operational voltage	600 V AC 50/60 Hz
[Ui] Rated Insulation Voltage	1000 V
Control type	Rotary handle
Type of operating handle	External right side External frontal
Mounting Support	Plate
[Uimp] rated impulse withstand voltage	12 kV IEC
Rated power in W	450 KW 400 V 560 KW 500 V 400 kW 690 V
Rated power in hp	200 Hp 240 V 480 A AC 500 Hp 480 V 477 A AC 500 hp 600 V 336 A AC
[Icw] rated short-time withstand current	75 kA
Mechanical durability	3500 cycles
Electrical durability	500 cycles
Connections - terminals	Lugs-ring terminals 2 0.05 in ² (34 mm ²) Bars 2 - busbar cross section: 40 x 5 mm
Height	12.60 in (320 mm)
Width	14.57 in (370 mm)
Depth	5.51 in (140 mm)

Environment

Standards	CSA C22.2 No 4 IEC 60947-3 UL98
Product Certifications	CE[RETURN]CSA[RETURN]JUL

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Ordering and shipping details

Category	22640-IEC DISCONNECT-GS1,LK3
Discount Schedule	I11
GTIN	3606480510489
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Styrene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes

Contractual warranty

Warranty	18 months
----------	-----------