

OCF Patio Infrared Heater



Grounded 3-pronged outlet (120V model)



NEMA 5-15R

Features

Finish

- Black anodized aluminum.

Voltage

- 120V, 240/208V, 60 Hz, 1-phase.

Construction

- Weatherproof IP65 certified for outdoor use.
- 2 mm wall thickness aluminum extrusion casing.
- High quality aluminum optical reflector.
- Pivoting wall mounting brackets included.
- Mounting brackets for ceiling suspension included (240/208V model).
- High quality power cord:
 - 120V Model: 7.5 ft. (2.25 m) with NEMA 5-15P plug.
 - 240/208V Model: 6 ft. (1.8 m) hard wire.

Heating element

- Woven carbon filament infrared lamp inside a 15 mm Quartz tube.
- Element service life \pm 5000h.

Wavelength

- Mid-wave (2 μ m).

Control

- On/Off integrated regulator and a remote control with 6 settings.

Certification

- Comply with the standard UL2021:2015 Ed.4 and C22.2 No.46: 2013 Ed.9.

Installation

- Installation minimum clearances: 8 ft. (2.4 m) from floor, 1 ft. (30 cm) from ceiling and 5 ft. (1.5 m) from the adjacent walls.
- Horizontal installation only.
- 120V Model:
 - Must be plugged into a grounded 3-pronged outlet, 15A, 120VAC.
 - Mounts on wall only.
- 240/208V Model:
 - Hard-wired into an electrical junction box (not included).
 - Mounts on wall or ceiling with the supplied mounting brackets.

Warranty

- 1-year warranty against defects.
- 90-day warranty on the element.

Application

- Temporary back-up heating, workshop, garage, solarium, pool and spa, balcony, patio, bar, restaurant, hotel, church.

Models

| Watts | Volts | Product # ¹ | Grounded 3-pronged outlet | Length in. | Length mm | Weight lb | Weight kg |
|-----------|---------|------------------------|---------------------------|------------|-----------|-----------|-----------|
| 1500 | 120 | CF15120B | 15A, 120VAC | 27 | 685.8 | 10.0 | 4.5 |
| 3000/2250 | 240/208 | CF30240B | - | 38 5/8 | 965.2 | 14.3 | 6.4 |

¹ Mounting brackets included.

