

PROJET:	DATE:
CAT. NO.:	TYPE:
NOTES	VOLTS:

GENERAL

Recessed fluorescent luminaire for T-grid ceilings. Clear acrylic prismatic diffuser (supplied as standard) is held within a hinged steel frame. Cam latch release opens frame for easy servicing; positive action, no springs. Retaining hook prevents the hinged frame from disengaging accidentally when open. No visible hardware. 4 1/4" deep housing reduces lamp shadow.

CONSTRUCTION

Rigid die-formed body constructed from code gauge steel.

FINISH

Standard finish is baked white enamel.

SHIELDING


No. K12 clear acrylic prismatic diffuser supplied as standard. Other options available.

ELECTRICAL

Instant start electronic ballast, 120V-50/60Hz. Other ballasts and voltages available upon request.

CERTIFICATIONS

CSA and/or UL approved.



Ordering Information

LACH	24G					
SERIES	SIZE	LAMPS	WATTS	SHIELDING	VOLTAGE	BALLAST / DRIVER
24G = 2' x 4'	1 = 1 2 = 2 3 = 3 4 = 4	14 = 14 (T5) 17 = 17 (T8) 24 = 24 (T8H0) 24 = 24 (T5HO) 28 = 28 (T5) 31 = 31 (U 1-5/8") 32 = 32 (T8) 32 = 32 (U 6") 40X = 40X (Biax) 54 = 54 (T5HO)	200 = #200 louver 12 = K12 lens 19 = K19 lens P2 = P2 louver P3 = P3 louver SLA = Acrylic silver louver	120 = 120 Volts 277 = 277 Volts 347 = 347 Volts	IS = IS PRS = PRS RS = RS	