



## Main

|                           |                                      |
|---------------------------|--------------------------------------|
| Product or Component Type | Mechanically Held Lighting Contactor |
| Range of Product          | 8903LX                               |
| Control Circuit           | Separate control circuit             |

## Complementary

|                       |   |
|-----------------------|---|
| Control Voltage       | 110 V AC 50 Hz<br>120 V AC 60 Hz              |
| Inrush power in VA    | 25 VA 60 Hz<br>140 VA 50 Hz<br>25 VA 50/60 Hz |
| Current Rating        | 20 A tungsten<br>30 A fluorescent             |
| Number of Poles       | 3P 3 NO                                       |
| Control Unit          | No control units                              |
| Pilot Light           | No indicator                                  |
| Other Options         | None  |
| Electrical Connection | Screw-clamp terminals                         |
| Height                | 8.82 in (224 mm)                              |
| Depth                 | 3.27 in (83 mm)                               |
| Width                 | 2.87 in (73 mm)                               |

## Environment

|                        |                         |
|------------------------|-------------------------|
| Enclosure Type         | Not rated (open device) |
| Product Certifications | UL Listed[RETURN]CSA    |

## Ordering and shipping details

|                   |                       |
|-------------------|-----------------------|
| Category          | 21322-8903 LX (NOT L) |
| Discount Schedule | CP1                   |
| GTIN              | 785901057284          |
| Returnability     | No                    |
| Country of origin | MX                    |

## Packing Units

|                              |                        |
|------------------------------|------------------------|
| Unit Type of Package 1       | PCE                    |
| Number of Units in Package 1 | 1                      |
| Package 1 Height             | 4.50 in (11.43 cm)     |
| Package 1 Width              | 7.40 in (18.796 cm)    |
| Package 1 Length             | 10.80 in (27.432 cm)   |
| Package 1 Weight             | 4.58 lb(US) (2.078 kg) |

## Offer Sustainability

|                             |  |
|-----------------------------|--|
| Sustainable offer status    | Green Premium product  |
| California proposition 65   | WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov |
| REACH Regulation            | <a href="#">REACH Declaration</a>                              |
| REACH free of SVHC          | Yes  |
| EU RoHS Directive           | Compliant <a href="#">EU RoHS Declaration</a>                  |
| Toxic heavy metal free      | Yes  |
| Mercury free                | Yes  |
| China RoHS Regulation       | <a href="#">China RoHS Declaration</a>                         |
| RoHS exemption information  | <a href="#">Yes</a>  |
| Environmental Disclosure    | <a href="#">Product Environmental Profile</a>                  |
| Circularity Profile         | No need of specific recycling operations                       |
| PVC free                    | Yes  |
| Halogen content performance | Halogen free plastic parts product                             |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|