



Main

Range of Product	Modicon Premium Automation platform
Product or Component Type	CANopen bus master PCMCIA card
Software Designation	CANopen standard
Software Version	V4.02
Additional information	Unauthorized on TSX P57 153M/154M processor
Electrical connection	1 male connector SUB-D 9 + TAP junction CANopen bus connection

Complementary

Product Compatibility	Modicon Premium TSXP57 Atrium TSXPCI or TPCX Device conforms to CANopen standard profile
Memory type	PCMCIA card III
Bus conformity class	M00
Communication port protocol	CANopen
Method of access	Master
Transmission Rate	800 kbit/s 500 kbit/s 125 kbit/s 20 kbit/s 10 kbit/s 1000 kbit/s 50 kbit/s 250 kbit/s
Transmission support medium	2 twisted shielded pairs cable
Communication Service	Message handling (SDO) Management of bus operating modes PDO cyclic exchanges
Number of modules per PLC per PC	1 Premium TSXP57
Current consumption	60 mA 5 V DC
Marking	CE
Net Weight	0.51 lb(US) (0.23 kg)

Environment

Ambient Air Temperature for Operation	32...140 °F (0...60 °C)
IP Degree of Protection	IP20
Standards	DR 303-2 DS 301 V4.02
Product Certifications	CSA[RETURN]UL
Protective treatment	Conformal coating Humiseal 1A33

Ordering and shipping details

Category	22558-TSX PREMIUM, ATRIUM & PL7 PRO
Discount Schedule	PC22
GTIN	3595863961447
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.57 in (4.0 cm)
Package 1 Width	6.69 in (17.0 cm)
Package 1 Length	8.66 in (22.0 cm)
Package 1 Weight	10.69 oz (303.0 g)

Contractual warranty

Warranty	18 months
----------	-----------