

T90 Nylon / TWN75 INSTAGLIDE®

10(19) T90/TWN75 CU RED

Contact

Inside Sales Representatives
Phone: 905-944-4300
buildingwire.canada@nexans.com

Nexans Ref.: 12000157

Country Ref.: 148577

EAN 13: 622089102743

600 Volts 90°C Cu PVC Insulated Nylon Covered Cables

DESCRIPTION

CSA File #LL23462 Class 5832 02

U.L. Standard #83 - U.L. Approval # E70347

Single copper conductor with thin wall PVC insulation and nylon covering with FT1 rating.

Rated 600 volts. LEAD FREE.

Nexans INSTAGLIDE® reduced friction construction in sizes 6 AWG and larger.

Colours: Standard colours are available.

T90 / TWN75 is **NOT** sunlight resistant.

Application

- General purpose building wire for installation as exposed or concealed wiring and in raceways (except cable trays) in dry or damp locations.
- Minimum recommended installation temperature minus 10°C (with suitable handling procedures).
- Maximum conductor temperature 90°C dry, 75°C in wet locations, and 60°C when exposed to oil.
- Approved for use with ceiling fixtures.

Harmonized Product Print Legend:

E53058 F INSTAGLIDE® 2/0 AWG (67.4mm²) (UL) THHN OR THWN-2 OR GR II OR MTW 600 VOLT VW-1 CT USE MADE IN CANADA LL 23462 2/0 AWG CSA/ACNOR T90 / TWN75 NYLON FT1

CHARACTERISTICS

Construction characteristics

Conductor material	Copper
Insulation	PVC and nylon
Jacket Colour	Red
With Bonding Conductor	No
With neutral or not	No

Dimensional characteristics

Approximate net weight	57.6 kg/km
Cable Diameter	4.2 mm
Conductor size (AWG)	10 AWG
Number of cores	1

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

Generated 2024-06-11 www.nexans.ca Page 1 / 2



STANDARDS

National CSA C22.2 N° 75

T90 Nylon / TWN75 INSTAGLIDE®

10(19) T90/TWN75 CU RED

Contact

Inside Sales Representatives

Phone: 905-944-4300

buildingwire.canada@nexans.com

Dimensional characteristics

Number of strands	19
-------------------	----

Electrical characteristics

Maximum operating voltage	600 V
---------------------------	-------

Usage characteristics

Maximum operating temperature	90 °C
-------------------------------	-------

Minimum installation temperature	-10 °C
----------------------------------	--------