
KS17, Split Bolt Connector, Run/Tap: #8 AWG Str-#6 AWG Sol

By Burndy
Catalog # KS17



Copper Split Bolt, Cu: 8 AWG (Str)-6 AWG (Sol) (Run & Tap), Length:1.14

Features

- UL467 Listed for Direct Burial applications in earth or concrete
- Compact, high-strength, copper alloy with free-running threads and easy to grip wrench flats
- Highly resistant to cracking and corrosion

Application

For Direct Burial Applications In Earth Or Concrete, Copper

Specifications

Certification - UL Recognized	No
Certification - cULus	No
EU RoHS Indicator	Yes
Industry Standard(s)	RUS
Certification - ETL	No
Standards - Industry Standards Met	RUS
Standards - RoHS Compliance Status	CM
Certification - UL Listed Direct Burial	Yes
UL Listed	Yes
Certification - CSA Approved	No

Conductor

Conductor - Copper Str Run Range	8 STR - 6 STR
Conductor - Copper Str Run	• 8 AWG • 7 AWG • 6 AWG
Conductor - Copper Solid Run Range	8 AWG-6 AWG
Conductor - Copper Solid Run	6 AWG
Conductor - Copper Solid Tap Range	14 AWG-6 AWG
Conductor - Copper Solid Tap	6 AWG
Conductor - CopperWeld Solid Tap Range	6 AWG
Conductor - CopperWeld Solid Tap	6 AWG
Conductor - CopperWeld Solid Run Range	6 AWG
Conductor - CopperWeld Solid Run	6 AWG
Conductor - CopperWeld Str Tap Range	9-1/2 D-3#12
Conductor - CopperWeld Str Tap	• 9-1/2 D • 8A • 3#12
Conductor - CopperWeld Str Run Range	9-1/2D -3#12
Conductor - CopperWeld Str Run	• 9-1/2D • 8A • 3#12
Conductor - CopperWeld Str Size Range	9-1/2 D-3#12
Conductor - CopperWeld Str Size	• 9-1/2 D • 8A • 3#12
Conductor Type	• CU C Solid-Run • CU C Str-Run • CU Weld C Solid-Run • CU Weld C Str-Run • CU C Str-Tap • CU Weld C Solid-Tap • CU Weld C Str-Tap • CU C Solid-Tap
Conductor - Copper Str Tap Range	8 STR - 6 STR
Conductor - Copper Str Tap	• 14 AWG • 12 AWG • 10 AWG • 9 AWG • 8 AWG • 7 AWG • 6 AWG

Configuration

Connector Type	Split Bolt

Dimensions

Package Height	0.000 in
Package Weight	0.000 lb.
Package Length	0.000 in
Package Width	0.000 in
Dimension - L Length Overall mm	29 mm
Width	0.45 in
Dimension - Width fraction	9/20 in
Dimension - B Length fraction	29/50 in

Dimension - Width mm	11 mm
Dimension - Width inch	0.45 in
Dimension - B Length inch	.58 in
Dimension - Cross Flats inch	0.63 in
Dimension - Length Overall inch	1.14

Force Related

Installation Torque Recommended in-lb	165 in

General

Trade Name	SERVIT®
Plated	N
Sub Brand	SERVIT
UPC	781810011508
Type	KS, Compact
Material	Copper
Plating Type	Unplated

UPC 12 Digit	781810011508
UPC 14 Digit GTIN	00781810011508

Logistics

Pallet Quantity	99000
Carton Quantity	100

Operational

Operating Temperature Celcius Max	90 °C
Operating Temperature Range Celcius	0 - 90
Operating Temperature Celcius Min	0 °C
Operating Temperature Range Fahrenheit	32 - 194

Product Assets

Catalog [English]

A Hubbell brand

© 2026 Hubbell Incorporated. All rights reserved