

PROJECT:	DATE:
CAT. NO.:	TYPE:
NOTES	VOLTS:

GENERAL

Surface mounted luminaire for indoor applications. Available in three widths to suit wide range of applications. Prismatic diffuser provides optimum light output. Suitable for continuous row mounting.

CONSTRUCTION

Rigid die-formed housing fabricated from code gauge steel.

FINISH

Standard finish is high gloss white polyester powder coat paint. Baked white enamel.

SHIELDING

Clear acrylic prismatic wrap-around diffuser supplied as standard. White opal diffuser available as option.

ELECTRICAL

Instant start electronic ballast, 120V-50/60Hz. Other ballasts and voltages available upon request.

CERTIFICATIONS

CSA and/or UL approved.



Ordering Information

PEL							
SERIES	DIFFUSER	MODULE WIDTH	MODULE LENGTH	LAMPS	WATTS	VOLTAGE	BALLAST / DRIVER
	C = Clear (C) O = Opal (O)	41 = 4 1/2" wide 51 = 7 1/8" wide 61 = 12 3/4" wide	2 = 2' 3 = 3' 4 = 4'	1 = 1 2 = 2 4 = 4	14 = 14 (T5) 17 = 17 (T8) 25 = 25 (T8) 28 = 28 (T5) 32 = 32 (T8)	120 = 120 Volts 277 = 277 Volts 347 = 347 Volts	IS = IS PRS = PRS RS = RS