

8539SCASP3

NEMA Combination Starter, Type S, HHL
electronic motor circuit protector, Size 1, 27A, 3
phase, 120VAC coil, NEMA 12



Main

Product	Combination Starter
Type	S
Control Circuit Type	Separate control circuit

Complementary

Control Circuit Voltage	110 V AC 50 Hz 120 V AC 60 Hz
Starter Type	Non reversing
Number of Poles	3P
Horsepower Rating	0.25...5 Hp 200 V AC, 3 phase 0.25...7.5 Hp 230 V AC, 3 phase 0.25...10 Hp 460 V AC, 3 phase 0.25...10 hp 575 V AC, 3 phase
Maximum Voltage Rating	600 V AC
Control Units	Selector switch HAND-OFF-AUTO)
Pilot Light	Red indicator on LED Green indicator off LED
Auxiliary Contacts	2 NO + 2 NC
Thermal overload type	Melting alloy 3
Disconnect Type	Circuit breaker, 30 A, electrical SPDT
Circuit breaker type	EMCP
Breaking capacity	100 KA 480 V AC 35 kA 600 V AC
Height	24.24 in (615.70 mm)
Depth	9.84 in (249.94 mm)
Width	9.62 in (244.35 mm)
Handle Swing	3.25 in (82.55 mm)

Environment

Enclosure Type	NEMA 12 painted sheet steel with external reset
NEMA size	1
Product Certifications	CSA file 584 class 3211 04[RETURN]UL listed file E152395 CCN NKJH[RETURN]UL listed file E152395 CCN NKJH7


Ordering and shipping details

Category	21213-8538,39 SC,SD(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	785901910602
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.00 in (30.48 cm)
Package 1 Width	14.00 in (35.56 cm)
Package 1 Length	32.50 in (82.55 cm)
Package 1 Weight	44.00 lb(US) (19.958 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Not compliant
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------