



Main

Range of Product	Homeline
Product or Component Type	Load Center
Line Rated Current	125 A
[Ue] rated operational voltage	120/240 V AC
Mounting Mode	Wall mount
Short-circuit current	10 kA

Complementary

Electrical Connection	Lugs
AWG gauge	AWG 6...AWG 2/0 aluminium/copper
Load center type	Main lugs
Number of spaces	30
Number of circuits	60
Number of tandem circuit breakers	30
Phase	1 phase
Cover type	Combination flush/surface cover
Device Composition	Grounding bar included (not installed)
Wiring configuration	3-wire
Material	Tin plated aluminium: busbar
Enclosure Material	Welded sheet steel
Cover colour	Grey
Box number	10
Height	33.75 in (857.25 mm)
Width	14.25 in (361.95 mm)
Depth	3.75 in (95.25 mm)

Environment

Product Certifications	CSA
NEMA degree of protection	NEMA 1 (indoor)
Ambient Air Temperature for Operation	23 °F (-5 °C) 104 °F (40 °C)

Ordering and shipping details

Category	00199-DE5 MISC. SERVICE PARTS
Discount Schedule	DE5
GTIN	785901463825
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	33.74 in (85.7 cm)
Package 1 Width	14.25 in (36.2 cm)
Package 1 Length	3.74 in (9.5 cm)
Package 1 Weight	31.00 lb(US) (14.061 kg)