

# aluminum

EXTRA-HEAVY  
**300**  
lb RATED  
DUTY



## EXTRA-HEAVY DUTY ALUMINUM EXTENSION

CSA Approved Grade 1, ANSI Type 1A

- Rigid "Box Section" side rails, unequalled for strength and durability
- Side-mounted rope pulley and slide guide system keeps rope clear of climber's feet and allows easy raising and lowering of the fly section
- Yellow ABS, high impact non-marring end caps
- Premium heavy duty rung locks
- Slip-resistant serrated "D" rungs for safe climbing and comfort
- Heavy duty ribbed swivel feet with ice pick
- 16' through 28' models have 2 7/8" x 7/8" side rails
- 32' through 44' models have 3 1/4" x 1" side rails

MODEL	SIZE	MAX. OPEN LENGTH	BASE SECTION		FLY SECTION		APPROX. WEIGHT lbs.
			OUTSIDE WIDTH	INSIDE WIDTH	OUTSIDE WIDTH	INSIDE WIDTH	
4216D	16'	13'	17"	15 1/4"	14 1/2"	12 3/4"	32
4220D	20'	17'	17"	15 1/4"	14 1/2"	12 3/4"	37
4224D	24'	21'	17"	15 1/4"	14 1/2"	12 3/4"	44
4228D	28'	25'	17"	15 1/4"	14 1/2"	12 3/4"	52
4232D	32'	29'	18 1/2"	16 1/2"	15 7/8"	13 7/8"	64
4236D	36'	32'	18 1/2"	16 1/2"	15 7/8"	13 7/8"	70
4240D	40'	35'	18 1/2"	16 1/2"	15 7/8"	13 7/8"	82
4244D	44'	39'	18 1/2"	16 1/2"	15 7/8"	13 7/8"	90
4360*	60'	50'	21 3/4"	19"	16"	14"	122

\*THREE SECTION EXTENSION, MIDDLE SECTION OUTSIDE WIDTH: 18 1/2", INSIDE WIDTH: 16 1/2"; ROUND RUNG; NOT CSA APPROVED

## EXTRA-HEAVY DUTY ALUMINUM EXTENSION

CSA Approved Grade 1, ANSI Type 1A

- Heavy duty "I" beam construction, 3 1/16" x 1 1/4" rails provide stability, torque resistance and high strength to weight ratio
- Heavy duty serrated "D" rungs prevent slipping for safe and sure climbing.
- Yellow ABS, high impact non-marring end caps
- Premium heavy duty rung locks
- Heavy duty ribbed swivel feet with ice picks

MODEL	SIZE	MAX. OPEN LENGTH	BASE SECTION		FLY SECTION		APPROX. WEIGHT lbs.
			OUTSIDE WIDTH	INSIDE WIDTH	OUTSIDE WIDTH	INSIDE WIDTH	
3216D	16'	13'	17 3/4"	15 1/4"	16 1/8"	13 5/8"	31
3220D	20'	17'	17 3/4"	15 1/4"	16 1/8"	13 5/8"	36
3224D	24'	21'	17 3/4"	15 1/4"	16 1/8"	13 5/8"	43
3228D	28'	25'	17 3/4"	15 1/4"	16 1/8"	13 5/8"	51
3232D	32'	29'	17 3/4"	15 1/4"	16 1/8"	13 5/8"	58
3236D	36'	32'	17 3/4"	15 1/4"	16 1/8"	13 5/8"	69
3240D	40'	35'	17 3/4"	15 1/4"	16 1/8"	13 5/8"	77



EXTRA-HEAVY  
**300**  
lb RATED  
DUTY

MEDIUM  
**225**  
lb RATED  
DUTY



## MEDIUM DUTY ALUMINUM EXTENSION

CSA Approved Grade 2, ANSI Type 2

- Sturdy extruded "C" channel construction
- Slip-resistant serrated "D" rungs for safe climbing and comfort
- Red, high impact, non-marring end caps
- Premium heavy duty rung locks
- Non-slip swivel feet

MODEL	SIZE	MAX. OPEN LENGTH	BASE SECTION		FLY SECTION		APPROX. WEIGHT lbs.
			OUTSIDE WIDTH	INSIDE WIDTH	OUTSIDE WIDTH	INSIDE WIDTH	
2216	16'	13'	15 7/8"	14 1/8"	15 1/8"	13 5/8"	20
2220	20'	17'	15 7/8"	14 1/8"	15 1/8"	13 5/8"	25
2224	24'	21'	15 7/8"	14 1/8"	15 1/8"	13 5/8"	32
2228	28'	25'	15 7/8"	14 1/8"	15 1/8"	13 5/8"	40
2232	32'	29'	15 7/8"	14 1/8"	15 1/8"	13 5/8"	48
2236	36'	32'	17 1/2"	15 1/4"	16 1/4"	13 7/8"	61
2240	40'	36'	17 1/2"	15 1/4"	16 1/4"	13 7/8"	68