



### Main

Product or component type	Automatic switch
Range of product	PowerPact L
Trip unit technology	Magnetic
Circuit breaker type	L-Frame

### Complementary

[In] rated current	400 A
[Ue] rated operational voltage	600 V AC
Mounting mode	Unit mount
Poles description	4P
Short-circuit withstand	65 kA 240 V conforming to UL 489 35 kA 480 V conforming to UL 489 18 kA 600 V conforming to UL 489
Breaking capacity code	G
Electrical connection	Lugs line Lugs load
AWG gauge	AWG 2/0...500 kcmil aluminum/copper)
Terminal identifier	AL600LS52K4
Magnetic tripping current	4800 A
Height	13.38 in (339.85 mm)
Width	5.51 in (139.95 mm)
Depth	6.61 in (167.89 mm)
Tightening torque	442.54 lbf.in (50 N.m) 0.11...0.37 in <sup>2</sup> (70...240 mm <sup>2</sup> ) AWG 2/0...500 kcmil)

### Environment

Product certifications	IEC CSA
------------------------	------------

## Packing Units

Package 1 Weight	15.00 lb(US) (6.804 kg)
------------------	-------------------------

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
PVC free	Yes