

Product data sheet

Characteristics

PHJ36020G

Plug-in unit, I-Line Busway, H-frame, 20A, 3 phase, 3 wire, 600VAC, 25kA, ground



Main

| | |
|---------------------------|--------------|
| Range of Product | I-Line |
| Product or Component Type | Plug-in unit |
| Module type | H-Frame |

Complementary

| | |
|--------------------------------|--|
| [Ue] rated operational voltage | 600 V AC 50/60 Hz |
| Phase | 3 phase |
| Busbar description | Ground |
| Fuse type | H |
| Breaking capacity code | J |
| Disconnecter device type | Thermal magnetic circuit breaker 20 A 25 kA 600 V Thermal magnetic circuit breaker 20 A 65 kA 480 V Thermal magnetic circuit breaker 20 A 100 kA 240 V |
| Level or class | Class 5600 |
| Wiring configuration | 3-wire |

Environment

| | |
|------------------------|---------------|
| Product Certifications | UL[RETURN]CSA |
|------------------------|---------------|

Ordering and shipping details

| | |
|-------------------|-----------------------------------|
| Category | 20183-PFH /PHG/PHJ/ PHL C/B PLUGS |
| Discount Schedule | PE7 |
| Returnability | No |

Packing Units

| | |
|------------------------------|--------------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 32.00 lb(US) (14.515 kg) |

Offer Sustainability

| | |
|---------------------------|---|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant with Exemptions |
| Mercury free | Yes |

| | |
|----------------------------|---|
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|
