

Fluorescent lampholders

Product description

Medium bi-pin
660W, 600V/AC

Features

- For replacement use in fluorescent lighting fixtures
- Use for flush or surface mounting
- Captive pal nut for easy mounting
- Push-in wire terminals feature release slots

Fluorescent lampholders



Rating		Description	Color	Catalog no.	
W	V/AC				
660	600	Standard, push wire, slide-on & screw switch	W	□ 2509W	•
		Short, push wire, slide-on & screw switch	W	□ 2510W	•
		Standard, screw terminals, screw switch	W	□ 924W†	

For panel cutout dimensional data, see Section Q-Technical Reference

† Not UL Listed or CSA certified

Pigtail lampholders

Product description

Medium base
660W, 250V/AC; 660W, 600V/AC

Features

- For use in electrical equipment, harnesses, light strings and related applications
- Wire leads are 5" (127.0mm) of color-coded stranded wire, stripped 1" (25.4mm) for easy connection
- Rubber sockets have an extended lip to seal against bulb
- Metal shell interiors are aluminum, 145 nickel plated copper with sealed leads where they enter husk


Pigtail lampholders




Rating		Description	Catalog no.	
W	V/AC			
660	250	Phenolic, wire size #14 AWG	□ 722*	•
660	600	Weatherproof rubber, wire size #14 AWG	□ 145	•

For panel cutout dimensional data, see Section Q-Technical Reference


*Only UL Listed



2509W



2510W



924W



722



145

Color information:

W (White)



(White)

Compliances, specifications and availability are subject to change without notice.

Indicates NAFTA compliant - Page Q-32

RoHS compliant - Page Q-32