

Rittal – The System.

Faster – better – everywhere.

Baying systems TS 8 – TS 8286.500

Date : Aug 5, 2016

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Baying systems TS 8 – TS 8286.500

: 05.08.2016 build on www.rittal.com/ca-en



Product description

Description:	The TS 8 sheet steel baying system, with its symmetrical profile in the width and depth, offers a significant space gain, plus simple interior installation. This likewise ensures bayability from all sides. Additionally, the integral, automatic potential equalisation of all enclosure panels and the triple surface treatment ensure optimum safety.
Material:	Enclosure frame: Carbon steel, 1.5 mm Roof: Carbon steel, 1.5 mm Door: Carbon steel, 2.0 mm Rear panel: Carbon steel, 1.5 mm Base plates: Carbon steel, 1.5 mm Mounting plate: Carbon steel, 3.0 mm
Surface finish:	Enclosure frame: Dipcoat-primed Door, roof and rear panel: Dipcoat-primed, powder-coated on the outside, textured paint Mounting plate and base plates: Zinc-plated
Color:	RAL 7035
Protection category IP to IEC 60 529:	IP 55
Protection category NEMA:	NEMA 12
IK code:	IK09
Supply includes:	Enclosure frame Door(s) Roof plate Rear panel, detachable 4 eyebolts Lock: 3 mm double-bit Base Plates Depth-adjustable mounting plate (with depth 500 mm)













2 Gleitschienen
2 support strips fitted in the enclosure depth

Packaging unit:	1 pc(s).
EAN:	4028177250949
Customs tariff number:	94032080
eCl@ss 5.1:	27180101
eCl@ss 7.0:	27180101
ETIM 6.0:	EC000261
Basic material:	Carbon steel



Product features






Dimensions:	Height: 1800 mm (71 ") Width: 1200 mm (47 ") Depth: 600 mm (24 ")
Mounting plate:	Height: 1696 mm (67 ") Width: 1099 mm (43 ")
Number of doors:	2
2 support strips fitted in the enclosure depth:	yes
Weight/pack:	179.9 kg

Approvals

Approvals:	 Bureau Veritas (EN)  CSA (EN)  Germanischer Lloyd (EN)  Lloyds Register of Shipping  Norske Veritas (EN)  Russian Maritime Register of Shipping (EN)  TUV EN  UL + C-UL (EN)
Certificates:	 IK-Code (EN)  Protection category (EN)
Declarations:	 Declaration of conformity (EN, DE)  Manufacturer's declaration 1 EN, DE

Downloads

Data sheets:  [Technical details](#)
EN
 [Technical system catalogue \(DE\)](#)

Documentation:  [Further information](#)
EN
 [Instructions](#)
FR, EN, DE
 [Load brochure](#)
EN, DE
 [PE conductor brochure](#)
EN, DE
 [White paper](#)
EN

Videos: Animation

CAD drawings: Request
