

**CRIMPFIX ECO****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

- For automatic stripping and crimping
- Time-saving and efficient processing
- Easily adjustable to the respective cross-section range
- Stripping and crimping in one work step
- The processing of sleeves or contacts from other manufacturers can cause machine failures and defects!

**General ordering data**

Version	Automatic machines, Automatic stripper and crimper
Order No.	<a href="#">2833890000</a>
Type	CRIMPFIX ECO
GTIN (EAN)	4064675422570
Qty.	1 pc(s).
Replacement parts	<a href="#">2875560000</a> <a href="#">2875570000</a>

Creation date November 26, 2024 12:20:40 PM CET

Catalogue status 26.11.2024 / We reserve the right to make technical changes.

**CRIMPFIX ECO****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

Depth	323 mm	Depth (inches)	12.717 inch
Height	188 mm	Height (inches)	7.402 inch
Width	230 mm	Width (inches)	9.055 inch
Net weight	12,496 g		

**PW65 maintenance - automatic stripping/crimping**

Consumables	Linked wire-end ferrules	Crimping	Trapezoidal
Crimping length	8 mm	Crimping range, max.	2.5 mm <sup>2</sup>
Crimping range, min.	0.5 mm <sup>2</sup>	Drive	Electro-mechanical
Electrical connection	100-240 V / 50/60 Hz / 100 VA	Length of wire-end ferrule	14 mm
Pulse time	approx. 1.5 s	Stripping range	0.5 - 2.5 mm <sup>2</sup> (~AWG 20-14)
Wire end ferrules cross-section, max.	2.5 mm <sup>2</sup>	Wire end ferrules cross-section, min.	0.5 mm <sup>2</sup>

**Classifications**

ETIM 6.0	EC002778	ETIM 7.0	EC002778
ETIM 8.0	EC002778	ETIM 9.0	EC002778
ECLASS 9.0	17-13-01-01	ECLASS 9.1	17-13-01-01
ECLASS 10.0	17-13-01-01	ECLASS 11.0	17-13-01-01
ECLASS 12.0	17-13-01-01	ECLASS 13.0	17-13-01-01
ECLASS 14.0	17-13-01-01		

**Environmental Product Compliance**

RoHS Compliance Status	Compliant with exemption
RoHS Exemption (if applicable/known)	6c, 7a, 7cl
REACH SVHC	Lead 7439-92-1
SCIP	d2df479e-2b79-4e98-adc7-b03577df98ae

**Approvals**

ROHS	Conform
------	---------

**Downloads**

User Documentation	<a href="#">OPIN CRIMPFIX ECO WEB</a>
Catalogues	<a href="#">Catalogues in PDF-format</a>