



## Main

Product or component type	Plug-in unit
Range of product	I-Line
Circuit breaker type	H-frame
Trip unit technology	Thermal-magnetic

## Complementary

Protection type	Circuit breaker
Mounting mode	Plug-in
[Ue] rated operational voltage	600 V AC
[In] rated current	125 A
Number of Phases	3 phases
Poles description	3P
Interrupt Rating	25 kA 240 V AC 18 kA 480 V AC 14 kA 600 V AC
[Ics] rated service short-circuit breaking capacity	80 %
Wiring configuration	4-wire (integral ground bus)
AWG gauge	AWG 8...AWG 3/0 1 phase and neutral AWG 6...AWG 2/0 1 ground
Depth	9.13 in (232 mm)
Height	8.50 in (216 mm)
Width	21.69 in (551 mm)

## Environment

Product certifications	CSA C22.2 No 27 UL listed file E22182
Standards	IEC 60529

UL 857

IP degree of protection

IP54

## Packing Units

Package 1 Weight

32.00 lb(US) (14.515 kg)

## Offer Sustainability

Sustainable offer status

Green Premium product

REACH Regulation

[REACH Declaration](#)

EU RoHS Directive

Compliant  
[EU RoHS Declaration](#)

Mercury free

Yes

RoHS exemption information

[Yes](#)

China RoHS Regulation

[China RoHS declaration](#)  
Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure

[Product Environmental Profile](#)