

Product Datasheet

Characteristic

CHU365SPLO

400A 3P Type1 600V Heavy Duty Non-Fusible Safety Switch With Lock-On Provision



Main

product or component type	Single Throw Safety Switch
disconnecter device type	Non-fusible disconnect
number of poles	3
electrical connection	Lugs
series name	Heavy duty

Complementary

Line Rated Current	400 A
device composition	None
device mounting	Surface
[Ue] rated operational voltage	600 V AC/DC
AWG gauge	AWG 1/0...750 kcmil copper or aluminium
Maximum Horse Power Rating	125 hp 240 V AC 50...60 Hz 3 phase NEC 430.52 250 hp 480 V AC 50...60 Hz 3 phase NEC 430.52 350 hp 600 V AC 50...60 Hz 3 phase NEC 430.52 50 hp 250 V DC 50 hp 600 V DC
height	50.25 in (1276.35 mm)
width	27.63 in (701.80 mm)
depth	10.13 in (257.30 mm)
tightening torque	550 lbf.in (62.14 N.m) AWG 1/0...750 kcmil)

Environment

product certifications	CSA
NEMA degree of protection	NEMA 1 galvanized steel

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	Free of Substances of Very High Concern above the threshold
REACH free of SVHC	Yes

EU RoHS Directive	Compliant
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	ENVPEP1404026EN