

# CHU365AWKEI

Safety switch, heavy duty, non fusible, 400A,  
600V, 3 poles, 350hp, NEMA 12, interlock



## Main

|                              |  |
|------------------------------|--|
| Range                        | Square D   |
| Product                      | Single Throw Safety Switch   |
| Current Rating               | 400 A  |
| Enclosure Rating             | NEMA 3R/12 galvanized steel  |
| Horsepower Rating            | 125 Hp at 240 V AC 50-60 Hz for 3 phase motors<br>250 Hp at 480 V AC 50-60 Hz for 3 phase motors<br>350 Hp at 600 V AC 50-60 Hz for 3 phase motors<br>50 Hp at 250 V DC<br>50 hp at 600 V DC |
| Disconnect Type              | Non-fusible disconnect   |
| Short Circuit Current Rating | 10 kA  |
| Mounting Type                | Surface  |
| Number of Poles              | 3  |
| Phase                        | 3 phase  |
| Certifications               | CSA  |
| Voltage Rating               | 600 V AC/DC  |
| Wire Configuration           | 4-wire   |
| Wire Size                    | AWG 1/0...750 kcmil copper or aluminium  |

## Complementary

|                   |  |
|-------------------|--|
| Tightening torque | 550 lbf.in (62.14 N.m) (AWG 1/0...750 kcmil) |
| Width             | 26.25 in (666.75 mm)                         |
| Height            | 46.25 in (1174.75 mm)                        |
| Depth             | 10.13 in (257.30 mm)                         |

## Ordering and shipping details

|                   |                                  |
|-------------------|----------------------------------|
| Category          | 00153-C,CH&CHU CANADA SW NON-NEG |
| Discount Schedule | DE1                              |
| Returnability     | No                               |
| Country of origin | MX                               |

## Packing Units

|                              |                   |
|------------------------------|-------------------|
| Unit Type of Package 1       | PCE               |
| Number of Units in Package 1 | 1                 |
| Package 1 Weight             | 0.16 oz (4.536 g) |

## Offer Sustainability

|                           |   |
|---------------------------|---|
| Sustainable offer status  | Green Premium product   |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| RECh Regulation           | <a href="#">RECh Declaration</a>  |
| EU RoHS Directive         | Compliant with Exemptions   |
| Mercury free              | Yes   |
| China RoHS Regulation     | <a href="#">China RoHS Declaration</a>  |

|                             |   |
|-----------------------------|---|
| RoHS exemption information  | <a href="#">Yes</a>                           |
| Environmental Disclosure    | <a href="#">Product Environmental Profile</a> |
| Circularity Profile         | No need of specific recycling operations      |
| PVC free                    | Yes   |
| Halogen content performance | Halogen free plastic parts product            |